



POINT 1R SQ 32

LL1227.BAMT400EC15 Stainless steel

GENERAL INFORMATION:

Installation Environment Outdoor, Indoor
 Type of fitting Recessed ceiling, Recessed in-ground
 Place of application Ceiling, In-Ground

CONSTRUCTIVE & DIMENSIONAL:

Construction material Stainless steel AISI 316L
 Length 32mm(1,25")
 Width 32mm(1,25")
 Height 2,5mm(0,09")
 Cutout shape Square
 Cutout diameter 36mm(1,41")
 Recessed depth 90mm(3,54")

ELECTRICAL:

Description 1 x 1.5W LED 4000K CRI>85 180 lm
 Operating Power [V/mA] 500mA
 Number of heads 1
 Control gear 500 mA not included
 Driver positioning Remote
 Control gear type Electronic
 Cord length [m] 0,5
 Emergency kit Not available

OPTICAL:

Beam type Medium (21° - 40°)
 Beam angle [°] 32°
 Light distribution Light distribution diffused
 Beam directionability Fixed
 Diffuser material Tempered glass
 Diffuser finish Opal

ACCESSORIES:

| | | | | |
|---|--|----------------------------------|--|--------------------------------------|
| | | | | |
| <p>Wall recessed rough-in housing 503 with adapter (32) AC295</p> | <p>Rough-in housing polypropilene (32) AC610</p> | <p>Rough-in housing Luc20580</p> | <p>LED DRIVER 500 mA IP67 AC206-IP67</p> | <p>IP 68 fast connector Luc22080</p> |