



POINT 1R SQ 32

LL1227.BAST400EC15 Stainless steel

GENERAL INFORMATION:

Installation Environment Outdoor, Indoor
 Type of fitting Recessed ceiling, Recessed in-ground
 Place of application Ceiling, In-Ground

CONSTRUCTIVE & DIMENSIONAL:

Construction material Stainless steel AISI 316L
 Length 32mm(1,25")
 Width 32mm(1,25")
 Height 2,5mm(0,09")
 Cutout shape Square
 Cutout diameter 36mm(1,41")
 Recessed depth 90mm(3,54")

ELECTRICAL:

Description 1 x 1.5W LED 4000K CRI>85 180 lm
 Operating Power [V/mA] 500mA
 Number of heads 1
 Control gear 500 mA not included
 Driver positioning Remote
 Control gear type Electronic
 Cord length [m] 0,5
 Emergency kit Not available

OPTICAL:

Beam type Narrow (11° - 20°)
 Beam angle [°] 16°
 Light distribution Light distribution diffused
 Beam directionability Fixed
 Diffuser material Tempered glass
 Diffuser finish Opal

ACCESSORIES:

Wall recessed rough-in housing 503 with adapter (32) AC295	Rough-in housing polypropilene (32) AC610	Rough-in housing Luc20580	LED DRIVER 500 mA IP67 AC206-IP67	IP 68 fast connector Luc22080

