

**POINT 1R AS SQ 32**

LL1439.BAXO300EC01	20506.01.31	White
LL1439.BAXO300EC19	20506.19.31	Light grey
LL1439.BAXO300EC02		Black
LL1439.BAXO300EC45	20506.45.31	Rust brown
LL1439.BAXO300EC15	20506.40.31	Stainless steel

**GENERAL INFORMATION:**

Installation Environment	Indoor
Type of fitting	Recessed wall
Place of application	Wall Lights
Application field	Hallways, Passageways, Stairs

**CONSTRUCTIVE & DIMENSIONAL:**

Length	32mm(1,25")
Width	32mm(1,25")
Cutout shape	Round
Cutout diameter	36mm(1,41")
Recessed depth	38mm(1,49")

**ELECTRICAL:**

Description	1 x 1W LED 3000K CRI>85 122 lm
Operating Power	350mA
Number of heads	1
Control gear	350 mA not included
Driver positioning	Remote
Control gear type	Electronic
Cord length	0.5 m
Emergency kit	Not available

**OPTICAL:**

Beam type	Extra wide (> 60°)
Beam angle [°]	80°
Light distribution	Asymmetric
Beam directionability	Fixed
Diffuser material	Polycarbonate

**LIGHTING SOURCE:**

Light source	LED
Power	1W
ZVEI - Led Type	LED module
Color temperature	3000K
Color rendering index	CRI>85
Nominal LED emission	122 lm
Light source	Included




**ADDITIONAL INFORMATION:**

Tested to ambient temperature

25°C

**ACCESSORIES:**



Rough-in housing  
polycarbonate  
AC201



Wall recessed  
rough-in housing  
503 with  
adapter  
AC295



LED driver  
350 mA  
IP20  
AC620



LED driver  
350 mA  
IP67  
AC620-IP67