

POINT 1R AS SQ 32

LL1439.BAXO400EL01	White
LL1439.BAXO400EL19	Light grey
LL1439.BAXO400EL02	Black
LL1439.BAXO400EL45	Rust brown
LL1439.BAXO400EL15	Stainless steel

GENERAL INFORMATION:

Installation Environment	Indoor
Type of fitting	Recessed wall
Place of application	Wall Lights
Application field	Hallways, Passageways, Stairs

CONSTRUCTIVE & DIMENSIONAL:

Length	32mm(1,25")
Width	32mm(1,25")
Cutout shape	Round
Cutout diameter	36mm(1,41")
Recessed depth	38mm(1,49")

ELECTRICAL:

Description	1 x 1W LED 4000K CRI>85 130 lm
Operating Power	24V DC
Number of heads	1
Number of circuits	1
Control gear	24 VDC not included
Driver positioning	Remote
Control gear type	Electronic
Cord length	0.5 m
Water-Lock system	Included
Emergency kit	Not available

OPTICAL:

Beam type	Extra wide (> 60°)
Beam angle [°]	80°
Light distribution	Asymmetric
Beam directionability	Fixed
Diffuser material	Polycarbonate

LIGHTING SOURCE:

Light source	LED
Power	1W
ZVEI - Led Type	LED module
Color temperature	4000K
Color rendering index	CRI>85
Nominal LED emission	130 lm
Light source	Included






ADDITIONAL INFORMATION:

Tested to ambient temperature

25°C

ACCESSORIES:



Rough-in housing
polycarbonate
AC201



Wall recessed
rough-in housing
503 with
adapter
AC295



LED driver
350 mA
IP20
AC620



LED driver
350 mA
IP67
AC620-IP67