



POINT 1R OR

| | | |
|-----------------------|-------------|--------------------|
| LL2050.BAM T400EC0150 | 20520.50.41 | Chrome |
| LL2050.BAM T400EC0101 | 20520.01.41 | White (matt) |
| LL2050.BAM T400EC0119 | 20520.19.41 | Silver grey (matt) |
| LL2050.BAM T400EC0122 | 20520.22.41 | Black (matt) |
| LL2050.BAM T400EC0145 | 20520.45.41 | Rust brown |

GENERAL INFORMATION:

| | |
|--------------------------|-------------------------------|
| Installation Environment | Indoor |
| Type of fitting | Recessed ceiling |
| Place of application | Path Lights, Ceiling |
| Application field | Passageways, Hallways, Stairs |

CONSTRUCTIVE & DIMENSIONAL:

| | |
|-----------------------|--|
| Construction material | Stainless steel AISI 316L, Steel, Mirror stainless steel, Anticorodal aluminum 6082 / stainless steel AISI 316L, Spun aluminum, Extruded aluminum EN AW-6060 T5 / die-casting alluminum EN-AB 44100, Technopolymer |
| Diameter | 45mm(1,77") |

ELECTRICAL:

| | |
|------------------------|---------------------|
| Recessed depth | 40mm(1,57") |
| Operating Power [V/mA] | 500mA |
| Number of heads | 1 |
| Control gear | 500 mA not included |
| Driver positioning | Remote |
| Control gear type | Electronic |
| Emergency kit | Not available |

OPTICAL:

| | |
|-----------------------|-----------------|
| Beam angle [°] | 32° |
| Light distribution | Direct lighting |
| Beam directionability | Swivelling |
| Rotation [°] | 15° |
| Diffuser finish | Opal |

ACCESSORIES:

