



**POINT 1 R OR**

LL2050.BAST300EC50	20521.50.31	Chrome
LL2050.BAST300EC01	20521.01.31	White (matt)
LL2050.BAST300EC19	20521.19.31	Silver grey (matt)
LL2050.BAST300EC22	20521.22.31	Black (matt)
LL2050.BAST300EC45	20521.45.31	Rust brown

**GENERAL INFORMATION:**

Installation Environment	Indoor
Type of fitting	Recessed ceiling
Place of application	Path Lights, Ceiling
Application field	Passageways, Hallways, Stairs

**CONSTRUCTIVE & DIMENSIONAL:**

Construction material	Die-cast aluminum EN AB 44100 highly resistant to oxidation
Diameter	45mm(1,77")
Cutout shape	Round
Recessed depth	40mm(1,57")

**ELECTRICAL:**

Description	1 x 1.5W LED 3000K CRI>85 200 lm
Operating Power [V/mA]	500mA
Number of heads	1
Control gear	500 mA not included
Driver positioning	Remote
Control gear type	Electronic
Cord length [m]	0.5
Emergency kit	Not available

**OPTICAL:**

Beam type	Narrow (11° - 20°)
Beam angle [°]	16°
Light distribution	Direct lighting
Beam directionability	Swivelling
Rotation [°]	15°

**ACCESSORIES:**



LED driver  
Luc22008

