



POINT 1R OR

LL2050.BAST400EC0150	20521.50.41	Chrome
LL2050.BAST400EC0101	20521.01.41	White (matt)
LL2050.BAST400EC0119	20521.19.41	Silver grey (matt)
LL2050.BAST400EC0122	20521.22.41	Black (matt)
LL2050.BAST400EC0145	20521.45.41	Rust brown

GENERAL INFORMATION:

Installation Environment	Indoor
Type of fitting	Recessed ceiling
Place of application	Path Lights, Ceiling
Application field	Passageways, Hallways, Stairs

CONSTRUCTIVE & DIMENSIONAL:

Construction material	Die-cast aluminum EN AB 44100 highly resistant to oxidation
Diameter	45mm(1,77")
Cutout shape	Round
Recessed depth	40mm(1,57")

ELECTRICAL:

Description	1 x 1.5W LED 4000K CRI>85 210 lm
Operating Power [V/mA]	500mA
Number of heads	1
Control gear	500 mA not included
Driver positioning	Remote
Control gear type	Electronic
Cord length [m]	0.5
Emergency kit	Not available

OPTICAL:

Beam type	Narrow (11° - 20°)
Beam angle [°]	16°
Light distribution	Direct lighting
Beam directionability	Swivelling
Rotation [°]	15°

ACCESSORIES:



LED driver
Luc22008