




POINT 1R RD 32

LL1007.BAST300EC15	20502.40.31	Frosted stainless steel
LL1007.BAST300EC01	20502.01.31	White (matt)
LL1007.BAST300EC19	20502.19.31	Silver grey (matt)
LL1007.BAST300EC22	20502.22.31	Black (matt)
LL1007.BAST300EC45	20502.45.31	Rust brown

GENERAL INFORMATION:

Installation Environment	Indoor
Type of fitting	Recessed ceiling, Recessed in-ground
Place of application	Path Lights, Ceiling



CONSTRUCTIVE & DIMENSIONAL:

Construction material	Stainless steel AISI 316L
Diameter	35mm(1,37")
Cutout shape	Round
Recessed depth	90mm(3,54")

ELECTRICAL:

Description	1 x 1.5W LED 3000K CRI>85 200 lm
Operating Power [V/mA]	500mA
Number of heads	1
Control gear	500 mA not included
Driver positioning	Remote
Control gear type	Electronic
Cord length [m]	0.5
Emergency kit	Not available

OPTICAL:

Beam type	Narrow (11° - 20°)
Beam angle [°]	16°
Light distribution	Light distribution diffused
Beam directionability	Fixed
Diffuser material	Tempered glass
Diffuser finish	Opal


ACCESSORIES:



LED driver
Luc22008



IP 68 fast
connector
Luc22080



Rough-in housing
Luc20580

