

POINT 2R AS SQ 45

LL1440.BAXO300EC01	20532.01.31	White
LL1440.BAXO300EC02		Black
LL1440.BAXO300EC19	20532.19.31	Light Grey
LL1440.BAXO300EC45	20532.45.31	Rust brown
LL1440.BAXO300EC15	20532.40.31	Stainless steel

GENERAL INFORMATION:

Installation Environment	Indoor
Type of fitting	Recessed wall
Place of application	Wall Lights
Application field	Hallways, Passageways, Stairs

CONSTRUCTIVE & DIMENSIONAL:

Length	45mm(1,77")
Width	45mm(1,77")
Cutout shape	Round
Cutout diameter	46mm(1,81")
Recessed depth	38mm(1,49")

ELECTRICAL:

Description	1 x 1W LED 3000K CRI>85 122 lm
Operating Power	350mA
Number of heads	1
Control gear	350 mA not included
Driver positioning	Remote
Control gear type	Electronic
Cord length	0.5 m
Emergency kit	Not available

OPTICAL:

Beam type	Extra wide (> 60°)
Beam angle [°]	80°
Light distribution	Asymmetric
Beam directionability	Fixed
Diffuser material	Polycarbonate

LIGHTING SOURCE:

Light source	LED
Power	1W
ZVEI - Led Type	LED module
Color temperature	3000K
Color rendering index	CRI>85
Nominal LED emission	122 lm
Light source	Included




ADDITIONAL INFORMATION:

Tested to ambient temperature

25°C

ACCESSORIES:



Rough-in housing
AC202



Wall recessed
rough-in housing
503 with
adapter AC296



LED driver
350 mA
IP20
AC620



LED driver
350 mA
IP67
AC620-IP67