



POINT 2R OR

LL2051.BAMT300EC50	20522.50.31	Chrome
LL2051.BAMT300EC01	20522.01.31	White (matt)
LL2051.BAMT300EC19	20522.19.31	Silver grey (matt)
LL2051.BAMT300EC22	20522.22.31	Black (matt)
LL2051.BAMT300EC45	20522.45.31	Rust brown

GENERAL INFORMATION:

Installation Environment	Indoor
Type of fitting	Recessed ceiling
Place of application	Path Lights, Ceiling
Application field	Passageways, Hallways, Stairs

CONSTRUCTIVE & DIMENSIONAL:

Construction material	Die-cast aluminum EN AB 44100 highly resistant to oxidation
Diameter	55mm(2,16")
Cutout shape	Round
Recessed depth	50mm(1,96")

ELECTRICAL:

Description	1 x 2W LED 3000K CRI>85 225 lm
Operating Power [V/mA]	700mA
Number of heads	1
Control gear	700 mA not included
Driver positioning	Remote
Control gear type	Electronic
Cord length [m]	0.5
Emergency kit	Not available

OPTICAL:

Beam type	Wide (41° - 60°)
Beam angle [°]	47°
Light distribution	Direct lighting
Beam directionability	Swivelling
Rotation [°]	15°

ACCESSORIES:



LED driver
Luc22014