



**POINT 2R OR**

LL2051.BAST400EC50	20523.50.41	Chrome
LL2051.BAST400EC01	20523.01.41	White (matt)
LL2051.BAST400EC19	20523.19.41	Silver grey (matt)
LL2051.BAST400EC22	20523.22.41	Black (matt)
LL2051.BAST400EC45	20523.45.41	Rust brown

**GENERAL INFORMATION:**

Installation Environment	Indoor
Type of fitting	Recessed ceiling
Place of application	Path Lights, Ceiling
Application field	Passageways, Hallways, Stairs

**CONSTRUCTIVE & DIMENSIONAL:**

Construction material	Die-cast aluminum EN AB 44100 highly resistant to oxidation
Diameter	55mm(2,16")
Cutout shape	Round
Recessed depth	50mm(1,96")

**ELECTRICAL:**

Description	1 x 2W LED 4000K CRI>85 240 lm
Operating Power [V/mA]	700mA
Number of heads	1
Control gear	700 mA not included
Driver positioning	Remote
Control gear type	Electronic
Cord length [m]	0.5
Emergency kit	Not available

**OPTICAL:**

Beam type	Narrow (11° - 20°)
Beam angle [°]	13°
Light distribution	Direct lighting
Beam directionability	Swivelling
Rotation [°]	15°

**ACCESSORIES:**



LED driver  
Luc22014