

### POINT 2R RD 45

LL1008.BAMT300EC40	20503.40.31	Frosted stainless steel
LL1008.BAMT300EC01	20503.01.31	White (matt)
LL1008.BAMT300EC19	20503.19.31	Silver grey (matt)
LL1008.BAMT300EC22	20503.22.31	Black (matt)
LL1008.BAMT300EC45	20503.45.31	Rust brown

### GENERAL INFORMATION:

Installation Environment	Indoor
Type of fitting	Recessed ceiling, Recessed in-ground
Place of application	Path Lights, Ceiling

### CONSTRUCTIVE & DIMENSIONAL:

Construction material	Stainless steel AISI 316L
Diameter	45mm(1,77")
Cutout shape	Round
Recessed depth	95mm(3,74")

### ELECTRICAL:

Description	1 x 2W LED 3000K CRI>85 225 lm
Operating Power [V/mA]	700mA
Number of heads	1
Control gear	700 mA not included
Driver positioning	Remote
Control gear type	Electronic
Cord length [m]	0.5
Emergency kit	Not available

### OPTICAL:

Beam type	Wide (41° - 60°)
Beam angle [°]	47°
Light distribution	Light distribution diffused
Beam directionability	Fixed
Diffuser material	Tempered glass
Diffuser finish	Opal


### ACCESSORIES:



LED driver  
Luc22014



IP 68 fast  
connector  
Luc22080



Rough-in housing  
Luc20581