

POINT 2R RD 45

LL1008.BAMT300EL40	Stainless steel
LL1008.BAMT300ELO1	White (matt)
LL1008.BAMT300EL19	Silver grey (matt)
LL1008.BAMT300EL22	Black (matt)
LL1008.BAMT300EL45	Rust brown

GENERAL INFORMATION:

Installation Environment	Indoor
Type of fitting	Recessed ceiling, Recessed in-ground
Place of application	Path Lights, Ceiling

CONSTRUCTIVE & DIMENSIONAL:

Construction material	Stainless steel AISI 316L
Diameter	45mm(1,77")
Cutout shape	Round
Recessed depth	95mm(3,74")

ELECTRICAL:

Description	1 x 2W LED 3000K CRI>85 225 lm
Operating Power [V/mA]	24V DC
Number of heads	1
Control gear	24 VDC not included
Driver positioning	Remote
Control gear type	Electronic
Cord length [m]	0.5
Water-Lock system	Included
Emergency kit	Not available

OPTICAL:

Beam type	Wide (41° - 60°)
Beam angle [°]	47°
Light distribution	Light distribution diffused
Beam directionability	Fixed
Diffuser material	Tempered glass
Diffuser finish	Opal


ACCESSORIES:



LED driver
Luc22014



IP 68 fast
connector
Luc22080



Rough-in housing
Luc20581