




**POINT 2R RD 45**

LL1008.BAST300EC40	20504.40.31	Stainless steel
LL1008.BAST300EC01	20504.01.31	White (matt)
LL1008.BAST300EC19	20504.19.31	Silver grey (matt)
LL1008.BAST300EC22	20504.22.31	Black (matt)
LL1008.BAST300EC45	20504.45.31	Rust brown

**GENERAL INFORMATION:**

Installation Environment	Indoor
Type of fitting	Recessed ceiling, Recessed in-ground
Place of application	Path Lights, Ceiling



**CONSTRUCTIVE & DIMENSIONAL:**

Construction material	Stainless steel AISI 316L
Diameter	45mm(1,77")
Cutout shape	Round
Recessed depth	95mm(3,74")

**ELECTRICAL:**

Description	1 x 2W LED 3000K CRI>85 225 lm
Operating Power [V/mA]	700mA
Number of heads	1
Control gear	700 mA not included
Driver positioning	Remote
Control gear type	Electronic
Cord length [m]	0.5
Emergency kit	Not available

**OPTICAL:**

Beam type	Narrow (11° - 20°)
Beam angle [°]	13°
Light distribution	Light distribution diffused
Beam directionability	Fixed
Diffuser material	Tempered glass
Diffuser finish	Opal


**ACCESSORIES:**



LED driver  
Luc22014



IP 68 fast  
connector  
Luc22080



Rough-in housing  
Luc20581

