

**POINT 2R SQ 45**

LL1228.BAMT400EC15      Stainless steel

**GENERAL INFORMATION:**

Installation Environment      Outdoor, Indoor  
 Type of fitting      Recessed ceiling, Recessed in-ground  
 Place of application      Ceiling, In-Ground

**CONSTRUCTIVE & DIMENSIONAL:**

Construction material      Stainless steel AISI 316L  
 Length      45mm(1,77")  
 Width      45mm(1,77")  
 Height      2,5mm(0,09")  
 Cutout shape      Square  
 Cutout diameter      46mm(1,81")  
 Recessed depth      95mm(3,74")

**ELECTRICAL:**

Description      1 x 2W LED 4000K CRI>85 240 lm  
 Operating Power [V/mA]      700mA  
 Number of heads      1  
 Control gear      700 mA not included  
 Driver positioning      Remote  
 Control gear type      Electronic  
 Cord length [m]      0,5  
 Emergency kit      Not available

**OPTICAL:**

Beam type      Wide (41° - 60°)  
 Beam angle [°]      47°  
 Light distribution      Light distribution diffused  
 Beam directionability      Fixed  
 Diffuser material      Tempered glass  
 Diffuser finish      Opal


**ACCESSORIES:**



Led driver 14W  
700mA  
AC624-IP67




IP 68 fast  
connector  
Luc22080



Rough-in  
housing  
Luc20581



Adaptor for installation  
like box 503  
AC296



Rough-in housing  
Luc611