

POINT 2R SQ 45

LL1228.BAST300EC15 Stainless steel

GENERAL INFORMATION:

Installation Environment Outdoor, Indoor
 Type of fitting Recessed ceiling, Recessed in-ground
 Place of application Ceiling, In-Ground

CONSTRUCTIVE & DIMENSIONAL:

Construction material Stainless steel AISI 316L
 Length 45mm(1,77")
 Width 45mm(1,77")
 Height 2,5mm(0,09")
 Cutout shape Square
 Cutout diameter 46mm(1,81")
 Recessed depth 95mm(3,74")

ELECTRICAL:

Description 1 x 2W LED 3000K CRI>85 225 lm
 Operating Power [V/mA] 700mA
 Number of heads 1
 Control gear 700 mA not included
 Driver positioning Remote
 Control gear type Electronic
 Cord length [m] 0,5
 Emergency kit Not available

OPTICAL:

Beam type Narrow (11° - 20°)
 Beam angle [°] 13°
 Light distribution Light distribution diffused
 Beam directionability Fixed
 Diffuser material Tempered glass
 Diffuser finish Opal


ACCESSORIES:



Led driver 14W
700mA
AC624-IP67




IP 68 fast
connector
Luc22080



Rough-in
housing
Luc20581



Adaptor for installation
like box 503
AC296



Rough-in housing
Luc611

