

**POINT 2R SQ 45**

LL1228.BAST400EC15                      Stainless steel

**GENERAL INFORMATION:**

Installation Environment                      Outdoor, Indoor  
 Type of fitting                                      Recessed ceiling, Recessed in-ground  
 Place of application                              Ceiling, In-Ground

**CONSTRUCTIVE & DIMENSIONAL:**

Construction material                              Stainless steel AISI 316L  
 Length    45mm(1,77")  
 Width    45mm(1,77")  
 Height    2,5mm(0,09")  
 Cutout shape                                        Square  
 Cutout diameter                                    46mm(1,81")  
 Recessed depth                                    95mm(3,74")

**ELECTRICAL:**

Description                                        1 x 2W LED 4000K CRI>85 240 lm  
 Operating Power [V/mA]                        700mA  
 Number of heads                                 1  
 Control gear                                        700 mA not included  
 Driver positioning                                Remote  
 Control gear type                                Electronic  
 Cord length [m]                                 0,5  
 Emergency kit                                     Not available

**OPTICAL:**

Beam type                                         Narrow (11° - 20°)  
 Beam angle [°]                                    13°  
 Light distribution                                Light distribution diffused  
 Beam directionability                         Fixed  
 Diffuser material                                Tempered glass  
 Diffuser finish                                    Opal


**ACCESSORIES:**



Led driver 14W  
700mA  
AC624-IP67




IP 68 fast  
connector  
Luc22080



Rough-in  
housing  
Luc20581



Adaptor for installation  
like box 503  
AC296



Rough-in housing  
Luc611