

**POINT 3R AS SQ 55**

|                    |             |                 |
|--------------------|-------------|-----------------|
| LL1441.BAXO300EC01 | 20534.01.31 | White           |
| LL1441.BAXO300EC02 |             | Black           |
| LL1441.BAXO300EC19 |             | Light Grey      |
| LL1441.BAXO300EC45 | 20534.45.31 | Rust brown      |
| LL1441.BAXO300EC15 | 20534.40.31 | Stainless steel |

**GENERAL INFORMATION:**

|                          |                               |
|--------------------------|-------------------------------|
| Installation Environment | Indoor                        |
| Type of fitting          | Recessed wall                 |
| Place of application     | Wall Lights                   |
| Application field        | Hallways, Passageways, Stairs |

**CONSTRUCTIVE & DIMENSIONAL:**

|                 |             |
|-----------------|-------------|
| Length          | 55mm(2,16") |
| Width           | 55mm(2,16") |
| Cutout shape    | Round       |
| Cutout diameter | 56mm(2,20") |
| Recessed depth  | 38mm(1,49") |

**ELECTRICAL:**

|                    |                                |
|--------------------|--------------------------------|
| Description        | 1 x 1W LED 3000K CRI>85 122 lm |
| Operating Power    | 350mA                          |
| Number of heads    | 1                              |
| Control gear       | 350 mA not included            |
| Driver positioning | Remote                         |
| Control gear type  | Electronic                     |
| Cord length        | 0.5 m                          |
| Emergency kit      | Not available                  |

**OPTICAL:**

|                       |                    |
|-----------------------|--------------------|
| Beam type             | Extra wide (> 60°) |
| Beam angle [°]        | 80°                |
| Light distribution    | Asymmetric         |
| Beam directionability | Fixed              |
| Diffuser material     | Polycarbonate      |

**LIGHTING SOURCE:**

|                       |            |
|-----------------------|------------|
| Light source          | LED        |
| Power                 | 1W         |
| ZVEI - Led Type       | LED module |
| Color temperature     | 3000K      |
| Color rendering index | CRI>85     |
| Nominal LED emission  | 122 lm     |
| Light source          | Included   |






**ADDITIONAL INFORMATION:**

Tested to ambient temperature

25°C

**ACCESSORIES:**



Rough-in housing  
AC200



Wall recessed  
rough-in housing  
503 with  
adapter AC297



LED driver  
350 mA  
IP20  
AC620



LED driver  
350 mA  
IP67  
AC620-IP67