

POINT 3R AS SQ 55

LL1441.BAXO400EC01	White
LL1441.BAXO400EC19	Light grey
LL1441.BAXO400EC02	Black
LL1441.BAXO400EC45	Rust brown
LL1441.BAXO400EC15	Stainless steel

GENERAL INFORMATION:

Installation Environment	Indoor
Type of fitting	Recessed wall
Place of application	Wall Lights
Application field	Hallways, Passageways, Stairs

CONSTRUCTIVE & DIMENSIONAL:

Length	55mm(2,16")
Width	55mm(2,16")
Cutout shape	Round
Cutout diameter	56mm(2,20")
Recessed depth	38mm(1,49")

ELECTRICAL:

Description	1 x 1W LED 4000K CRI>85 130 lm
Operating Power	350mA
Number of heads	1
Control gear	350 mA not included
Driver positioning	Remote
Control gear type	Electronic
Cord length	0.5 m
Emergency kit	Not available

OPTICAL:

Beam type	Extra wide (> 60°)
Beam angle [°]	80°
Light distribution	Asymmetric
Beam directionability	Fixed
Diffuser material	Polycarbonate

LIGHTING SOURCE:

Light source	LED
Power	1W
ZVEI - Led Type	LED module
Color temperature	4000K
Color rendering index	CRI>85
Nominal LED emission	130 lm
Light source	Included




ADDITIONAL INFORMATION:

Tested to ambient temperature

25°C

ACCESSORIES:



Rough-in housing
polycarbonate
AC200



Wall recessed
rough-in housing
503 with
adapter AC297



LED driver
350 mA
IP20
AC620



LED driver
350 mA
IP67
AC620-IP67