



POINT 3R OR

LL2052.BGMT400EC0150	20524.50.41	Chrome
LL2052.BGMT400EC0101	20524.01.41	White (matt)
LL2052.BGMT400EC0119	20524.19.41	Silver grey (matt)
LL2052.BGMT400EC0122	20524.22.41	Black (matt)
LL2052.BGMT400EC0145	20524.45.41	Rust brown

GENERAL INFORMATION:

Installation Environment	Indoor
Type of fitting	Recessed ceiling
Place of application	Ceiling
Application field	Passageways, Hallways, Stairs

CONSTRUCTIVE & DIMENSIONAL:

Construction material	Die-cast aluminum EN AB 44100 highly resistant to oxidation
Diameter	65mm(2,55")
Cutout shape	Round
Recessed depth	60mm(2,36")

ELECTRICAL:

Description	1 x 3W LED 4000K CRI>85 335 lm
Operating Power [V/mA]	1050mA
Number of heads	1
Control gear	1050 mA not included
Driver positioning	Remote
Control gear type	Electronic
Cord length [m]	0.5
Emergency kit	Not available

OPTICAL:

Beam type	Medium (21° - 40°)
Beam angle [°]	37°
Light distribution	Direct lighting
Beam directionability	Swivelling
Rotation [°]	15°

ACCESSORIES:



LED driver
Luc22017