



**POINT 3R OR**

LL2052.BGST400EC0150	20525.50.41	Chrome
LL2052.BGST400EC0101	20525.01.41	White (matt)
LL2052.BGST400EC0119	20525.19.41	Silver grey (matt)
LL2052.BGST400EC0122	20525.22.41	Black (matt)
LL2052.BGST400EC0145	20525.45.41	Rust brown

**GENERAL INFORMATION:**

Installation Environment	Indoor
Type of fitting	Recessed ceiling
Place of application	Ceiling
Application field	Passageways, Hallways, Stairs

**CONSTRUCTIVE & DIMENSIONAL:**

Construction material	Die-cast aluminum EN AB 44100 highly resistant to oxidation
Diameter	65mm(2,55")
Cutout shape	Round
Recessed depth	60mm(2,36")

**ELECTRICAL:**

Description	1 x 3W LED 4000K CRI>85 335 lm
Operating Power [V/mA]	1050mA
Number of heads	1
Control gear	1050 mA not included
Driver positioning	Remote
Control gear type	Electronic
Cord length [m]	0.5
Emergency kit	Not available

**OPTICAL:**

Beam type	Extra narrow (0° - 10°)
Beam angle [°]	10°
Light distribution	Direct lighting
Beam directionability	Swivelling
Rotation [°]	15°

**ACCESSORIES:**



LED driver  
Luc22017