



POINT 3R RD 55

LL1009.AHFT400EC40	20508.40.31	Stainless steel
LL1009.AHFT400EC01	20508.01.31	White (matt)
LL1009.AHFT400EC19	20508.19.31	Silver grey (matt)
LL1009.AHFT400EC22	20508.22.31	Black (matt)
LL1009.AHFT400EC45	20508.45.31	Rust brown

GENERAL INFORMATION:

Installation Environment	Indoor
Type of fitting	Recessed ceiling, Recessed in-ground
Place of application	Path Lights, Ceiling

CONSTRUCTIVE & DIMENSIONAL:

Construction material	Stainless steel AISI 316L
Diameter	55mm(2,16")
Cutout shape	Round
Recessed depth	100mm(3,93")


ELECTRICAL:

Description	1 x 6W LED 3000K CRI>90 845 lm
Operating Power [V/mA]	350mA
Number of heads	1
Control gear	350 mA not included
Driver positioning	Remote
Control gear type	Electronic
Cord length [m]	0.5
Emergency kit	Not available

OPTICAL:

Beam type	Extra wide (> 60°)
Beam angle [°]	62°
Light distribution	Light distribution diffused
Beam directionability	Fixed
Diffuser material	Polycarbonate

ACCESSORIES:



Fci [\] b \ ci gbl ' @V&\$) , &



@8 Xf] Yf @V&&\$%\$

