



POINT 3R RD 55

LL1009.BGMT300EC40	20510.40.31	Stainless steel
LL1009.BGMT300EC01	20510.01.31	White (matt)
LL1009.BGMT300EC19	20510.19.31	Silver grey (matt)
LL1009.BGMT300EC22	20510.22.31	Black (matt)
LL1009.BGMT300EC45	20510.45.31	Rust brown

GENERAL INFORMATION:

Installation Environment	Indoor
Type of fitting	Recessed ceiling, Recessed in-ground
Place of application	Path Lights, Ceiling

CONSTRUCTIVE & DIMENSIONAL:

Construction material	Stainless steel AISI 316L
Diameter	55mm(2,16")
Cutout shape	Round
Recessed depth	100mm(3,93")


ELECTRICAL:

Description	1 x 3W LED 3000K CRI>85 315 lm
Operating Power [V/mA]	1050mA
Number of heads	1
Control gear	1050 mA not included
Driver positioning	Remote
Control gear type	Electronic
Cord length [m]	0.5
Emergency kit	Not available

OPTICAL:

Beam type	Medium (21° - 40°)
Beam angle [°]	37°
Light distribution	Light distribution diffused
Beam directionability	Fixed
Diffuser material	Polycarbonate

ACCESSORIES:



Fci [\] b \ ci gb [' @V&\$) , &



@8 Xf] Yf @V&\$\$%

