

POINT 3R SQ 55

LL1229.AHMT300EC15 Stainless steel

GENERAL INFORMATION:

Installation Environment Outdoor, Indoor
Type of fitting Recessed ceiling, Recessed in-ground
Place of application Ceiling, In-Ground

CONSTRUCTIVE & DIMENSIONAL:

Construction material Stainless steel AISI 316L
Length 55mm(2,16")
Width 55mm(2,16")
Height 2,5mm(0,09")
Cutout shape Square
Cutout diameter 56mm(2,20")
Recessed depth 100mm(3,93")

ELECTRICAL:

Description 1 x 6W LED 3000K CRI>90 845 lm
Operating Power [V/mA] 350mA
Number of heads 1
Control gear 350mA not included
Driver positioning Remote
Control gear type Electronic
Cord length [m] 0,5
Emergency kit Not available

OPTICAL:

Beam type Medium (21° - 40°)
Beam angle [°] 28°
Light distribution Light distribution diffused
Beam directionability Fixed
Diffuser material Tempered glass
Diffuser finish Opal


ACCESSORIES:



@X Xfj Yf') \$'a 5
'D' +
57* &\$! D' +




D*, Zgh
Vtbb Yitf
@V&&\$, \$



Fci [\!]b \ci gbl
@V&(\$), &



5XUdtef Zf] jgtu' Utjcb']YVcl) \$'
@V&- +



Fci [\!]b \ci gbl
@VW%&

