

POINT 3R SQ 55

LL20567.40.31	Stainless steel
LL20567.01.31	White (matt)
LL20567.19.31	Silver grey (matt)
LL20567.22.31	Black (matt)
LL20567.45.31	Rust brown

GENERAL INFORMATION:

Installation Environment	Outdoor, Indoor
Type of fitting	Recessed ceiling, Recessed in-ground
Place of application	Ceiling, In-Ground



CONSTRUCTIVE & DIMENSIONAL:

Construction material	Stainless steel AISI 316L
Length	55mm(2,16")
Width	55mm(2,16")
Height	2,5mm(0,09")
Cutout shape	Square
Cutout diameter	56mm(2,20")
Recessed depth	100mm(3,93")

ELECTRICAL:

Operating Power [V/mA]	1050mA
Number of heads	1
Control gear	1050 mA not included
Driver positioning	Remote
Control gear type	Electronic
Emergency kit	Not available

OPTICAL:

Beam type	Extra narrow (0° - 10°)
Beam angle [°]	10°
Light distribution	Light distribution diffused
Beam directionability	Fixed
Diffuser material	Tempered glass
Diffuser finish	Opal


ACCESSORIES:



④X'8fj] Yf
%\$) \$'a 5'
57&%\$



④8'8F=9F
%\$) \$'a 5
57&%\$!-D* +



Fci [\!]b\ci gb[
@V&\$) , &

