

**POINT 3R SQ 55**

LL1229.BGMT300EC15      Stainless steel

**GENERAL INFORMATION:**

Installation Environment      Outdoor, Indoor  
 Type of fitting      Recessed ceiling, Recessed in-ground  
 Place of application      Ceiling, In-Ground

**CONSTRUCTIVE & DIMENSIONAL:**

Construction material      Stainless steel AISI 316L  
 Length      55mm(2,16")  
 Width      55mm(2,16")  
 Height      2,5mm(0,09")  
 Cutout shape      Square  
 Cutout diameter      56mm(2,20")  
 Recessed depth      100mm(3,93")

**ELECTRICAL:**

Description      1 x 3W LED 3000K CRI>85 315 lm  
 Operating Power [V/mA]      1050mA  
 Number of heads      1  
 Control gear      1050 mA not included  
 Driver positioning      Remote  
 Control gear type      Electronic  
 Cord length [m]      0,5  
 Emergency kit      Not available

**OPTICAL:**

Beam type      Medium (21° - 40°)  
 Beam angle [°]      37°  
 Light distribution      Light distribution diffused  
 Beam directionability      Fixed  
 Diffuser material      Tempered glass  
 Diffuser finish      Opal


**ACCESSORIES:**



LED DRIVER  
1050 mA  
AC210-IP67




IP 68 fast  
connector  
Luc22080



Rough-in housing  
Luc20582



Adaptor for installation like box  
503  
Luc297



Rough-in housing  
Luc612

