

POINT 3R SQ 55

LL1229.BGST300EC15 Stainless steel

GENERAL INFORMATION:

Installation Environment Outdoor, Indoor
 Type of fitting Recessed ceiling, Recessed in-ground
 Place of application Ceiling, In-Ground

CONSTRUCTIVE & DIMENSIONAL:

Construction material Stainless steel AISI 316L
 Length 55mm(2,16")
 Width 55mm(2,16")
 Height 2,5mm(0,09")
 Cutout shape Square
 Cutout diameter 56mm(2,20")
 Recessed depth 100mm(3,93")

ELECTRICAL:

Description 1 x 3W LED 3000K CRI>85 315 lm
 Operating Power [V/mA] 1050mA
 Number of heads 1
 Control gear 1050 mA not included
 Driver positioning Remote
 Control gear type Electronic
 Cord length [m] 0,5
 Emergency kit Not available

OPTICAL:

Beam type Extra narrow (0° - 10°)
 Beam angle [°] 10°
 Light distribution Light distribution diffused
 Beam directionability Fixed
 Diffuser material Tempered glass
 Diffuser finish Opal


ACCESSORIES:



LED DRIVER
1050 mA
AC210-IP67




IP 68 fast
connector
Luc22080



Rough-in housing
Luc20582



Adaptor for installation like box
503
Luc297



Rough-in housing
Luc612

