

POINT 3R SQ 55

| | |
|---------------|--------------------|
| LL20570.40.31 | Stainless steel |
| LL20570.01.31 | White (matt) |
| LL20570.19.31 | Silver grey (matt) |
| LL20570.22.31 | Black (matt) |
| LL20570.45.31 | Rust brown |

GENERAL INFORMATION:

| | |
|--------------------------|--------------------------------------|
| Installation Environment | Outdoor, Indoor |
| Type of fitting | Recessed ceiling, Recessed in-ground |
| Place of application | Ceiling, In-Ground |



CONSTRUCTIVE & DIMENSIONAL:

| | |
|-----------------------|---------------------------|
| Construction material | Stainless steel AISI 316L |
| Length | 55mm(2,16") |
| Width | 55mm(2,16") |
| Height | 2,5mm(0,09") |
| Cutout shape | Square |
| Cutout diameter | 56mm(2,20") |
| Recessed depth | 100mm(3,93") |

ELECTRICAL:

| | |
|------------------------|---------------------|
| Operating Power [V/mA] | 350mA |
| Number of heads | 1 |
| Control gear | 350 mA not included |
| Driver positioning | Remote |
| Control gear type | Electronic |
| Emergency kit | Not available |

OPTICAL:

| | |
|-----------------------|-----------------------------|
| Beam type | Wide (41° - 60°) |
| Beam angle [°] | 55° |
| Light distribution | Light distribution diffused |
| Beam directionability | Fixed |
| Diffuser material | Tempered glass |
| Diffuser finish | Opal |


ACCESSORIES:



Led driver 350 mA
IP67
AC620-IP67



LED DRIVER 350 mA
IP20
AC620



Rough-in housing
Luc20582

