







Clear and Color lens

#### PRODUCT FEATURES:

LED dimmable suspended pendant in die cast aluminum

120 degree beam angle

Delivered Lumens: 1450lm
Power Consumption: 12W
Dimming Compatibility: 0-10V
Input Voltage: 110-277V
Output: 350mA

#### SIZE (KK):

Diameter: Ø2,75"

Length of LED housing:3,86"

Length of the lens Code: 01. 2"

02. 4" 03. 6"

04. 8"

05. 10"

06. 12" 07. 14"

08. 16"

09. 18"

10. 24"

Custom sizes available on request\*

### ROD (FF):

101. Clear102. Frosted

103. Bubble Acrylic

All acrylic rod comes with frosted bottom\*

### TYPE OF INSTALLATION (SS):

201. Cable Suspension202. Stem Suspension

Cable suspension will include standard field-cuttable 60" suspension cable. For longer lengths, please consult BYIBA. (Please proceed with caution with field-cutting cable).

203. Surface-mounted204. Catenary-mounted

205. Recessed

sales@gordonbullard.com www.cerchiolighting.com 1 877-964-4646



991 South Gull Lake Dr Richland, MI 49083, USA 1 877-964-4646



### **BIG** G





# BO-1001-(KK)-(FF)-(SS)-(LL)-(MM)-(TT)-(QQ)-(WW)

### STEM SUSPENSION LENGTHS (LL):

 301.
 6"
 304.
 24"

 302.
 12"
 305.
 30"

 303.
 18"
 306.
 36"

For longer and/or custom lengths, please consult BYIBA Customer Service.\*

#### LED HOUSING FINISH(MM):

401.Black 403.Silver or Aluminum 405.White

402.Bronze 404.Champagne (Matted Gold)

# LAMP TYPE (TT):

501. 3000K/82 CRI 502. 3500K/82 CRI 503. 4000K/82 CRI

504. (LED-A) LED w/ Amber Lens 505. (LED-B) LED w/ Blue Lens 506. (LED-C) LED w/ Red Lens

## DRIVERS(QQ):

601. Dimmable TRIAC:

-input voltage 100-240(277vac) -output voltage 27-42 vdc -out current 350mA -size 119 x 40 x 27mm

602. Non Dimmable:

-input voltage 100-120 vac -output voltage 25-40 vdc -out current 350mA -size 72 x 77 x 29mm

# INSTALLATION TYPE/RATE (WW):

701. Indoor 702. Outdoor

sales@gordonbullard.com www.cerchiolighting.com 1 877-964-4646



991 South Gull Lake Dr Richland, MI 49083, USA 1 877-964-4646