



LIGHTING SOURCE:

Light source:	LED	
Power:	12W: for model	GH1447.BRXT300EN 1447.BRX.T.15 GH1447.BRXT400EN 1447.BSX.T.15
	6W: for model	GH1447.AHXT300EN 1447.LVX.T.15 GH1447.AHXT400EN 1447.LZX.T.15
LED voltage range:	31.2-36.8V	
Current:	12W - 350 mA 6W - 180 mA	
ZVEI - Led Type:	LED	
Color temperature:	3000K for model	GH1447.BRXT300EN 1447.BRX.T.15
	4000K for model	GH1447.BRXT400EN 1447.BSX.T.15
	3000K for model	GH1447.AHXT300EN 1447.LVX.T.15
	4000K for model	GH1447.AHXT400EN 1447.LZX.T.15
Binning:	Step MacAdam 3	
Color rendering index:	CRI>90	
Nominal LED emission:	1469 lm for model	GH1447.BRXT300EN 1447.BRX.T.15
	1492 lm for model	GH1447.BRXT400EN 1447.BSX.T.15
	788 lm for model	GH1447.AHXT300EN 1447.LVX.T.15
	801 lm for model	GH1447.AHXT400EN 1447.LZX.T.15
Light source:	Included	
Ambient temperature operating range:	-20 °C ÷ +35 °C	

FINISH CODE:

 .15 Stainless Steel

ACCESSORIES:

