



D44 INDICO 215 narrow (DALI)



CONSTRUCTIVE:

Installation type:	Ground recessed
Environments:	Urban landscape, façades and architectural works, wellness, hallway, conference hall, places of worship, residential lighting
Mounting type:	With rough-in housing
Mounting note:	On normally inflammable surfaces allowed.
Body:	Corrosion resistant die-cast aluminium body and dome.
Painting:	Polyester powder coating, with a pluri-processed against corrosion (passed the exposure of over 1500 hours in a saline mist environment).
Screws:	AISI 304 stainless steel screws.
Seals:	Silicone Rubber.
Static load:	2000Kg
Standard Colour:	AL aluminium grey
Option colors:	GR graphite satin finish

ELECTRICAL:

Item code:	D44K/P2-LWWNB-DD-AL D44K/P2-LWNNB-DD-AL
Ballast type:	DALI.
Frequency:	50-60Hz
Lifetime:	50.000h L80B10 (T _a =25°C)
Line input:	Pre-wired and tested with resin sealed watertight H07RN-F five poles cable.
Mounting ballast type:	Integral
Voltage:	110-277 V
Separate ignition:	No
Emergency 1E:	No
Emergency 3E:	No

OPTICAL:

Diffuser:	Unbreakable UV-resistant polycarbonate.
Beam:	Narrow
Emission:	Direct
Adjustable:	Yes



LIGHTING SOURCE for model D44K/P2-LWWNB-DD-AL

MacAdam:	Step 3
Nominal Flux:	0
Output Flux:	323 lm
Source type:	LED
System power:	10W
Temperature Colour:	3000K CRI>80



BYIBA

L I G H T



D44 INDICO 215 narrow


LIGHTING SOURCE for model D44K/P2-LWNNB-DD-AL

MacAdam:	Step 3
Nominal Flux:	0
Output Flux:	342 lm
Source type:	LED
System power:	10W
Temperature Colour:	4000K CRI>80

DIMENSIONS:


Total diameter device (mm) 215(8,46")

PHOTOMETRICS:



D44K/P2-LWNNB-DD-AL

h (m)	Ø (m)	$\gamma=0.0$ $\alpha=\beta=17^\circ$	Emed (lx)
10.00	1.87		68
8.00	1.50		92
6.00	1.12		164
4.00	0.75		370
2.00	0.37		1530



D44K/P2-LWNNB-DD-AL

h (m)	Ø (m)	$\gamma=0.0$ $\alpha=\beta=17^\circ$	Emed (lx)
10.00	1.87		71
8.00	1.50		99
6.00	1.12		171
4.00	0.75		387
2.00	0.37		1544

ACCESSORIES:

Electrical

ACS/CR7

IP68 connector plug and socket terminal for cable
 $\text{Ø}7-12\text{mm} - 5 \times 0,5-1,5\text{mm}^2$.



ACS/FX05

3 ways IP68 wiring box for DALI
 looping connection.



g@gordonbullard.com

byiba.com

1-877-964-4646



991 South Gull Lake Dr

Richland, MI 49083

USA