



ABACO-P 200 (pendant)

BY-51170-P



PROJECT

SPEC TYPE

NOTES



GENERAL INFORMATION:

Our modern and minimalist pendant lighting fixtures are crafted from aluminum die-casting with an electrostatic powder coating. Measuring Ø 7.9" (20 cm) x H 1.6" (4 cm), they come in white black and grey finishes. These LED fixtures operate at 110-277V with a 28W output, offering color temperatures of 3000K, 4000K, and 5000K, and CRI options of 80 or 90. Designed for pendant mounting, they are ETL certified and ideal for indoor use.

HOUSING:

AL. Die-Casting, Electrostatic Powder Coating

FINISHING:

White, Black, Grey

LIGHTING:

LED (SMD)

INPUT VOLTAGE:

110-277V

IP RATING:

20

OPERATING TEMPERATURE RANGE:

-20 to +40 C

COVER:

PC

WIRE:

PVC













WWW.BULLARDCOLLECTION.COM

<u>TECHNICAL</u>

<u>OUTDOOR</u>





CONTACT US:

sales@gordonbullard.com www.byiba.com 1 877-964-4646


WE WELCOME ALL CUSTOM ORDERS




PROJECT

SPEC TYPE

NOTES















HOW TO ORDER:

Example:

CODE: BY-51170-P-01-K30-80-BL-RE

CODE:

BY-51170-P-01-K30-80-

BL-RE

1 MODEL:

-01 A) Diameter- Ø: 7.9" (20 cm) B) Height - H: 1.6" (4 cm)

C,D) Canopy - Ø: 4.33" (11 cm) x H: 1.6" (4 cm)

-02 A) Diameter- Ø: 7.9" (20 cm)
B) Height - H: 1.6" (4 cm)
C) Canopy - Ø: 3.9" (10 cm)

2 LIGHT SOURCE:

28W - LED - 700 mA - 2 281 lm

3 CCT SPECIFY:

-K30 3000K -K40 4000K -K50 5000K

4 CRI:

-80 CRI 80 -90 CRI 90

5 FINISH OPTIONS:

-BL Black -GR Grey -WH White

6 DRIVER POSITION:

-RE Remove

WWW.BULLARDCOLLECTION.COM

<u>TECHNICAL</u>

<u>OUTDOOR</u>

<u>DECORATIVE</u>



CONTACT US:


sales@gordonbullard.com www.byiba.com 1 877-964-4646




PROJECT

SPEC TYPE

NOTES















HOW TO ORDER:

Example:

CODE: BY-51170-P-01-K30-80-BL-RE

CODE:

BY-51170-P-06-K30-80-BL-RE

9 PHOTOMETRIC:

3 000 K			
90° 180° 90°	h(m)	E(lx)	D(mm) 109.7°
60°	1	822	2839
45°	2	206	5679
cd/1000lm C180 C0-	3	91	8518

WWW.BULLARDCOLLECTION.COM





CONTACT US:

sales@gordonbullard.com www.byiba.com 1 877-964-4646