

CAMBIO COLLECTION (track)

BY-50-TR



SPEC TYPE

NOTES



GENERAL INFORMATION:

The Cambio Track Collection features a versatile DC Track System with sleek linear track heads, perfect for modern interiors. Made from aluminum with an electrostatic powder coating, the low-voltage 48V track system is available in three profile options: Surface-Mounted S, Surface-Mounted L, and Recessed, with sizes of 39.4" (100 cm), 78.7" (200 cm), and 118" (300 cm). The system and linear track heads come in black and white finishes. Equipped with LED light sources, the linear track heads offer CCT options of 3000K, 4000K, and 5000K, with CRI choices of 80 or 90, ensuring high-quality, customizable lighting

MATERIAL:

AL, Electrostatic Powder Coating

FINISHING:

White, Black

LIGHTING:

LED

VOLTAGE:

Low Voltage Track (48V)

IP RATING:

20

OPERATING TEMPERATURE RANGE:

-20 to +40 C













WWW.BULLARDCOLLECTION.COM

<u>TECHNICAL</u> <u>OUTDOOR</u>

DECORATIVE





CONTACT US:



SPEC TYPE

NOTES



HOW TO ORDER:

Example:

CODE: BY-50-TR-1-01-65020-03-K30-C80-B1-WL

CODE:

BY-50-TR-1-01-6502 0-03-K30-C80-B1-WL

1 CHOOSE TRACK MODEL:

Surface-Mounted S profile



-1-01 L: 39.4" (100 cm)

-1-02 L: 78.7" (200 cm)

-1-03 L:118" (300 cm)

Surface-Mounted L profile



-2-01 L: 39.4" (100 cm)

-2-02 L: 78.7" (200 cm)

-2-03 L:118" (300 cm)

Recessed profile



-3-01 L: 39.4" (100 cm)

-3-02 L: 78.7" (200 cm)

-3-03 L:118" (300 cm)













WWW.BULLARDCOLLECTION.COM






CONTACT US:



SPEC TYPE

NOTES





















HOW TO ORDER:

Example:

CODE: BY-50-TR-1-01-65560-01-K30-C80-WL

CODE:

BY-50-TR-1-01-6502 0-03-K30-C80-B1-WL

1 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - -65560-01

Dimensions: L: 9.65" (24.5 cm) x H: 0.87" (2.2 cm)
Housing: AL. Extrude, Electrostatic Powder Coating

Cover: Lens Light Source: LED (SMD) Power: 12W

Lumens: 698 lm (3000K)

Output Current 350 mA

CCT: K30 - 3000K

K40 - 4000K K50 - 5000K

CRI: C80 - 80

C90 - 90

Finish options: -WL - White

-BL - Black

Operating temperature range - -20 to +40°C

Maintenance of lumen - L80 - 50 000 hours at 25 °C

WWW.BULLARDCOLLECTION.COM

TECHNICAL

OUTDOOR

DECORATIVE




CONTACT US:



SPEC TYPE

NOTES



















HOW TO ORDER:

Example:

CODE: BY-50-TR-1-01-65560-01-K30-C80-WL

CODE:

BY-50-TR-1-01-6502 0-03-K30-C80-B1-WL

CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE --65560-02

L: 9.65" (24.5 cm) x H: 0.87" (2.2 cm) Dimensions: AL. Extrude, Electrostatic Powder Coating Housing:

Cover: PC

LED (SMD) Light Source: 10W Power: Output Current 350 mA

CCT: K30 - 3000K

> K40 - 4000K K50 - 5000K

CRI: C80 - 80

C90 - 90

-WL - White Finish options:

-BL - Black

Operating temperature range - -20 to +40°C

Maintenance of lumen - L80 - 50 000 hours at 25 °C

WWW.BULLARDCOLLECTION.COM

TECHNICAL OUTDOOR DECORATIVE





CONTACT US:



SPEC TYPE

NOTES

















HOW TO ORDER:

Example:

CODE: BY-50-TR-1-01-65560-01-K30-C80-WL

CODE:

BY-50-

TR-1-01-65560-01-K30-C80-WL

1 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - 59100

Dimensions: L: 38" (96.6 cm) x H: 0.87" (2.2 cm) x W: 0.91 (2.3 cm)

Housing: AL. Extrude & AL. Die-Casting,

Electrostatic Powder Coating

Cover PC

Light Source: LED (SMD)
Power: 28W

Lumens: 1 924 lm (3000K)

CCT: -K30 - 3000K

-K40 - 4000K -K50 - 5000K

CRI: -C80 - 80

-C90 - 90

Finish options: -WL - White


-BL - Black

Operating temperature range - -20 to +40°C

Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:

3 000 K



WWW.BULLARDCOLLECTION.COM

TECHNICAL

OUTDOOR

DECORATIVE



CONTACT US: