

FLOW 60 (cylinders)

BY-27610-CL



PROJECT

SPEC TYPE

NOTES



GENERAL INFORMATION:

The Cylinder Flow 60 recessed downlight fixture features a modern, minimalist design made from durable metal. Available in three models —Small, Medium, and Big—with dimensions Ø 2.36" (6 cm) x H 4.3" (11 cm), Ø 2.36" (6 cm) x H 5.3" (13.4 cm), and Ø 2.36" (6 cm) x H 6.35" (16 cm), respectively. It comes in Black, White, and Grey finishes. The fixture is equipped with an LED light source, available in 15W, 19W, and 24W power options, and offers color temperatures of 3000K or 4000K. Designed for recessed mounting, it operates at 110-277V, is ETL certified, and is perfect for indoor environments.

MATERIAL:

AL. Die-Casting, Electrostatic Powder Coating

FINISHING:

White, Grey, Black







LIGHTING:

LED

INPUT VOLTAGE:

110-277V

IP RATING:

20

OPERATING TEMPERATURE RANGE:

-20 to +40 C

REFLECTOR:

Lens

















WWW.BULLARDCOLLECTION.COM

<u>TECHNICAL</u>

<u>OUTDOOR</u>





CONTACT US:

sales@gordonbullard.com www.byiba.com 1 877-964-4646


WE WELCOME ALL CUSTOM ORDERS





PROJECT

SPEC TYPE

NOTES



















HOW TO ORDER:

Example:

CODE: BY-27610-CL-01-B1-K30-80-BL

CODE:

BY-27610-CL-01-B1-K30-80-BL

1 MODEL:

-01 A) Diameter - Ø: 2.36" (6 cm)
B) Height - H: 4.3" (11 cm)
C) Mounting base - Ø: 4.2" (10.7 cm)

-02 A) Diameter - Ø: 2.36" (6 cm)
B) Height - H: 5.3" (13.4 cm)
C) Mounting base - Ø: 4.2" (10.7 cm)

-06 A) Diameter - Ø: 2.36" (6 cm)
B) Height - H: 6.35" (16 cm)
C) Mounting base - Ø: 4.2" (10.7 cm)

2 LIGHT SOURCE:

For 01 model

-W24 LED / 24W / 600 mA

For 02 model

-W15 LED / 15W / 350 mA

For 06 model (zoom type)

-W19 LED / 19W / 450 mA

3 BEAM ANGLE - LUMINOUS FLUX:

-B1-1 23.5° 2 610 lm

-B1-2 31° 2 623 lm For 01 model

-B1-3 47.2° 2 676 lm

-B2-1 26° 2 387 lm

-B2-1 20 2 307 IIII For 02 model

-B3 23.6° - 32.8° For 06 model

WWW.BULLARDCOLLECTION.COM

<u>TECHNICAL</u>

<u>OUTDOOR</u>

<u>DECORATIVE</u>



CONTACT US:


sales@gordonbullard.com www.byiba.com 1 877-964-4646





PROJECT

SPEC TYPE

NOTES

















HOW TO ORDER:

Example:

CODE: BY-27610-CL-01-B1-K30-80-BL

CODE:

BY-27610-CL-01-B1-K30-80-BL

CCT SPECIFY:

-K30 3000K -K40 4000K

5 CRI:

-80 **CRI 80** -90 **CRI 90**

FINISH OPTIONS:

-BL Black -GR Grey -WH White

DRIVER POSITION:


Remove

PHOTOMETRICS: 8

For 01 model

		180 90	h(m)	E(lx)	D(mm) 23.5°			
	60	500	1	11667	417			
74	XX	#	2	2917	833			
3 000 K	15" 39 cd/1000(m	34 15° C100 C0	3	1296	1250			
Name of Street	90	180 90	h(m)	E(lx)	D(mm)			
	HOW	KX			31.0°			
	**X	60"	1	8258	555			
	15 XA	A 35	2	2064	1111			
3 000 K	d/1000lm	0160 CO	3	918	1666			
	90	180 90	h(m)	E(lx)	D(mm)			
_	17/h	WY-			47.2°			
	60 XX	1000	1	3928	873			
	45	45						
	XX	XX	2	982	1746			
3 000 K	d/1000lm	25 T15°	3	436	2619			

For 02 model



For 06 model

		A	h(m)	E(lx)	D(mm) 23.6°
-	45	60	1	5783	418
Z	XA	U+X	2	1446	835
Zoom IN	d/1000lm	2848 15° C160 C0-	3	643	1253
	90	180 90	h(m)	E(lx)	D(mm)
	1777	# XXX	1		32.8°
	60	100	1	4571	589
And the second	NA.	250 15	2	1143	1178

WWW.BULLARDCOLLECTION.COM

TECHNICAL OUTDOOR





CONTACT US:

sales@gordonbullard.com www.byiba.com 1 877-964-4646