



FLOW 83 (cylinders)

BY-27620-CL



PROJECT

SPEC TYPE

NOTES















GENERAL INFORMATION:

The cylinder Flow 83 recessed downlight fixture features a modern, minimalist design crafted from durable metal. This fixture comes in one model with dimensions of \varnothing 3.3" (8.3 cm) x H 5.1" (13 cm) and is available in Black, White, and Grey finishes. It utilizes a 32W LED light source with color temperature options of 3000K or 4000K, operating at 110-277V. Designed for recessed mounting, this ETL-certified light is perfect for indoor environments.

HOUSING:

AL. Die-Casting, Electrostatic Powder Coating

FINISHING:

White, Grey, Black







LIGHTING:

LED

INPUT VOLTAGE:

110-277V

IP RATING:

20

OPERATING TEMPERATURE RANGE:

-20 to +40 C

REFLECTOR:

Lens

WWW.BULLARDCOLLECTION.COM

TECHNICAL



DECORATIVE



CONTACT US:


sales@gordonbullard.com www.byiba.com 1 877-964-4646



PROJECT

SPEC TYPE

NOTES













HOW TO ORDER:

Example:

CODE: BY-27620-CL-B1-K30-80-BL

CODE:

BY-27620-CL-B1-

K30-80-BL

1 DIMENSIONS:

A) Diameter - Ø: 3.3" (8.3 cm)
B) Height - H: 5.1" (13 cm)
C) Mounting base - Ø: 5.3" (13.5 cm)

2 LIGHT SOURCE:

LED / 32W / 800 mA

3 BEAM ANGLE - LUMINOUS FLUX:

-B1 19.9° 3 380 lm -B2 31.2° 3 535 lm -B3 47.9° 3 452 lm

4 CCT SPECIFY:

-K30 3000K -K40 4000K

5 CRI:

-80 CRI 80 -90 CRI 90

6 FINISH OPTIONS:

-BL Black -GR Grey -WH White

7 DRIVER POSITION:

Remove

WWW.BULLARDCOLLECTION.COM

TECHNICAL OUTDOOR





CONTACT US:


sales@gordonbullard.com www.byiba.com 1 877-964-4646



PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

Example:


CODE: BY-27620-CL-B1-K30-80-BL

CODE:

BY-27620-CL-B1-K30-80-BL

PHOTOMETRIC:

3 000 K



1280 -15°

1779

1250

555 2668







WWW.BULLARDCOLLECTION.COM

TECHNICAL OUTDOOR DECORATIVE



CONTACT US:

sales@gordonbullard.com www.byiba.com 1 877-964-4646