



MOND 850 (pendant)

BY-51330-P



PROJECT

SPEC TYPE

NOTES



GENERAL INFORMATION:

Our modern and minimalist lighting fixtures come in pendant and ceiling models. They feature an aluminum extruded housing with electrostatic powder coating and a steel gear box. Measuring Ø 27.55" (85 cm) x H 3.2" (8.1 cm), they are available in white, black and grey finishes. These LED fixtures operate at 110-277V with a wattage of 35W, offering CCT options of 3000K, 4000K, and 5000K, and CRI options of 80 or 90. ETL certified, they are ideal for indoor use in both residential and commercial spaces.

HOUSING:

HOSING - AL. Extrude, Electrostatic Powder Coating

GEAR BOX - Steel, Electro Powder Coating

COVER - PC UGR 16

FINISHING:

Black, Grey, White

LIGHTING:

LED SMD

INPUT VOLTAGE:

110-277V

IP RATING:

20

OPERATING TEMPERATURE RANGE:

-20 to +40 C

WIRE:

STS













WWW.BULLARDCOLLECTION.COM

<u>TECHNICAL</u>

<u>OUTDOOR</u>

<u>DECORATIVE</u>



CONTACT US:

sales@gordonbullard.com www.byiba.com 1 877-964-4646


WE WELCOME ALL CUSTOM ORDERS




PROJECT

SPEC TYPE

NOTES

















HOW TO ORDER:

Example:

CODE: BY-51330-P-01-K30-80-RE-BL

CODE:

BY-51330-P-01-K30-80-RE-BL

MODEL:

-01 Ø: 33.45" (85 cm) A) Diameter-B) Height -3.2" (8.1 cm) Ø: 2.36" (6 cm) C) Canopy

-01-02 A) Diameter-Ø: 33.45" (85 cm) B) Height 3.2" (8.1 cm) C) Canopy Ø: 16.14" (40.6 cm)

LIGHT SOURCE:

LED - 80W - 700 mA - 8 876 lm

CCT SPECIFY:

3000K -K30 -K40 4000K -K57 5000K

CRI:

-80 **CRI 80** -90 **CRI 90**

DRIVER POSITION:

-RE Remove

FINISH OPTIONS:

-BL Black -GR Grey White -WH

WWW.BULLARDCOLLECTION.COM

TECHNICAL OUTDOOR





CONTACT US:


sales@gordonbullard.com www.byiba.com 1 877-964-4646




PROJECT

SPEC TYPE

NOTES

















HOW TO ORDER:


Example:

CODE: BY-51330-P-01-K30-80-RE-BL

CODE:

BY-51330-P-01-K30-80-RE-BL

9 PHOTOMETRIC:



WWW.BULLARDCOLLECTION.COM





CONTACT US:

sales@gordonbullard.com www.byiba.com 1 877-964-4646