



SILO 175 SMD (cylinders) BY-51021-CL



PROJECT

SPEC TYPE

NOTES



GENERAL INFORMATION:

Our modern and minimalist pendant and ceiling lighting fixtures are crafted from aluminum die-casting with electrostatic powder coating, measuring Ø 6.9" (17.5 cm) x H 9" (23 cm). Available in dark, black, and grey finishes, these fixtures feature SMD LEDs, operating at 27W, 28W, 35W, or 41W with a voltage range of 110-277V. They offer color temperatures of 3000K, 4000K, and 5000K (SMD only) with CRI options of 80 and 90. Non-dimmable and suitable for both pendant and ceiling mounting, these ETL-certified fixtures are designed for indoor use in residential and commercial environments.

HOUSING

AL. Die-Casting, Electrostatic Powder Coating

FINISHING:

White, Black, Grey

LIGHTING:

LED (SMD)

INPUT VOLTAGE:

110-277V

IP RATING:

20

OPERATING TEMPERATURE RANGE:

-20 to +40 C

COVER:

PC

WIRE:

STS / PVC













WWW.BULLARDCOLLECTION.COM

<u>TECHNICAL</u>







CONTACT US:

sales@gordonbullard.com www.byiba.com 1 877-964-4646


WE WELCOME ALL CUSTOM ORDERS




PROJECT

SPEC TYPE

NOTES

















HOW TO ORDER:

Example:

CODE: BY-51021-CL-03-K30-80-P-BL-RE

CODE:

BY-51021-CL-03-K30-80-P-BL-RE

1 MODEL:

-03 A) Diameter - Ø: 6.9" (17.5 cm) B) Height - H: 9" (23 cm)

C) Canopy - Ø: 3.5" (9 cm) x H: 1" (2.5 cm)

-03-02 A) Diameter - Ø: 6.9" (17.5 cm) B) Height - H: 9" (23 cm)

2 LIGHT SOURCE:

LED SMD - 18W - 500 mA - 1214 lm

3 CCT SPECIFY:

-K30 3000K

-K40 4000K

-K50 5000K

4 CRI:

-80 CRI 80

-90 CRI 90

5 INSTALLATION TYPE:

-P Pendant

-C Ceiling

6 FINISH OPTIONS:

-BL Black

-GR Grey

-WH White

WWW.BULLARDCOLLECTION.COM

<u>TECHNICAL</u>

<u>OUTDOOR</u>

<u>DECORATIVE</u>



CONTACT US:


sales@gordonbullard.com www.byiba.com 1 877-964-4646




PROJECT

SPEC TYPE

NOTES

















HOW TO ORDER:

Example:

CODE: BY-51021-CL-03-K30-80-P-BL-RE

BY-51021-CL-03-K30-80-

CODE:

7 DRIVER POSITION:

-RE

P-BL-RE

-RE Remove

8 PHOTOMETRICS:

SMD 18W 3 000 K			
90° 180° 90°	h(m)	E(I x)	D(mm) 100 . 6°
60° 60° 45°	1	499	2410
45°	2	125	4820
cd/1000lm C180 C0	3	55	7229

WWW.BULLARDCOLLECTION.COM



DECORATIVE



CONTACT US:

sales@gordonbullard.com www.byiba.com 1 877-964-4646