



SILO 74 (cylinders)

BY-51400-CL



**PROJECT** 

SPEC TYPE

**NOTES** 

















#### **GENERAL INFORMATION:**

Our modern and minimalist pendant and ceiling lighting fixtures, made from durable aluminum die-casting with an electrostatic powder coating, are perfect for contemporary interiors. Available in dark, black, and grey finishes, these fixtures feature a COB LED that operates at 20W with a voltage range of 110-277V, offering color temperatures of 3000K (warm white) or 4000K (cool white) with CRI options of 80 or 90. They are non-dimmable and can be mounted as pendant or ceiling lights. ETL certified and designed for indoor use, they are ideal for both residential and commercial spaces. The fixtures come with a 5-year limited warranty.

#### **HOUSING:**

AL. Die-Casting, Electrostatic Powder Coating

#### FINISHING:

White, Black, Grey

#### LIGHTING:

LED (COB)

### **INPUT VOLTAGE:**

110-277V

#### **IP RATING:**

20

#### **OPERATING TEMPERATURE RANGE:**

-20 to +40 C

#### **REFLECTOR:**

ABS (Chrome)

## WIRE:

**PVC** 

## WWW.BULLARDCOLLECTION.COM

<u>TECHNICAL</u>

<u>OUTDOOR</u>

<u>DECORATIVE</u>



**CONTACT US:** 

sales@gordonbullard.com www.byiba.com 1 877-964-4646


WE WELCOME ALL CUSTOM ORDERS





**PROJECT** 

SPEC TYPE

NOTES







## whisper in eyes

NON GLARE REFLECTOR













### **HOW TO ORDER:**

Example:

CODE: BY-51400-CL-01-20W-B1-K30-80-P-BL-RE

# CODE:

BY-51400-CL-01-20W-B1-K30-80-P-BL-RE

-01

-20W

-B1

-K30

-80

-P

#### 1 MODEL:

-01

A) Diameter- Ø: 2.9" (7.4 cm)
B) Height - H: 4.72" (12 cm)

C) Canopy Ø: 2.3"(6 cm) x H: 1" (2.5 cm)

-02 A) Diameter- Ø: 2.9" (7.4 cm)
B) Height H: 4.72" (12 cm)
C) Canopy Ø: 2" (5.2 cm)

01-02 A) Diameter- Ø: 2.9" (7.4 cm) B) Height H: 4.72" (12 cm)

## 2 LIGHT SOURCE:

-20W LED - 20W - 500 mA

## 3 BEAM ANGLE - LUMINOUS FLUX:

-B1 21.8° 1 535 lm -B2 28.5° 1 526 lm

-B3 40.0° 1 708 lm

### 4 CCT SPECIFY:

-K30 3000K -K40 4000K

#### 5 CRI:

-80 CRI 80 -90 CRI 90

## 6 INSTALLATION TYPE:

-P Pendant -C Ceiling

-SM Surface Mounted

#### WWW.BULLARDCOLLECTION.COM

<u>TECHNICAL</u>

<u>OUTDOOR</u>

<u>DECORATIVE</u>



**CONTACT US:** 


sales@gordonbullard.com www.byiba.com 1 877-964-4646





**PROJECT** 

**SPEC TYPE** 

**NOTES** 









NON GLARE REFLECTOR













## **HOW TO ORDER:**

Example:

CODE: BY-51400-CL-01-20W-B1-K30-80-P-BL-RE



BY-51400-CL-01-20W-B1-K30-80-P-BL-RE

-BL

-RE

# FINISH OPTIONS:

-BL Black -GR Grey

-WH


-RE

DRIVER POSITION:

Remove

White

# PHOTOMETRICS:



90° 180° 90°	h(m)	E(Ix)	D(mm) 21.8°
60°	1	8245	385
45°	2	2061	769
15° 3466 15° cd/1000lm C180 C0-	3	916	1154

E(lx) D(mm)







90° 180° 90°	h(m)	E(lx)	D(mm) 40.0°
60°/	1	4127	729
45°	2	1032	1458
15° 1735 15° cd/1000lm C180 C0—	3	459	2187

### WWW.BULLARDCOLLECTION.COM

**TECHNICAL OUTDOOR** 

**DECORATIVE** 



**CONTACT US:** 

sales@gordonbullard.com www.byiba.com 1 877-964-4646