

TORCH R (cylinders)

BY-2015-CL



**PROJECT** 

SPEC TYPE

**NOTES** 



#### GENERAL INFORMATION:

The Torch Collection Cylinder Lighting Fixture offers a sleek, minimalist design with two versatile mounting options: recessed and pendant. Made from durable aluminum and finished with epoxy-polyester coating, it comes in silk white or matte black finishes. Featuring an anodized aluminum inner ring (black or bronze) and a 26° aspherical glass lens, it delivers precise light control. The recessed version is available in two sizes: Ø 1.5" x H 3.9" and Ø 1.5" x H 9.8". It features an 8.6W COB LED light source (1100 lm, CRI>90) and offers color temperatures of 2700K, 3000K, and 4000K. The fixture is IP20 rated for indoor use and comes with optional 0-10V dimming or non-dimmable options.

### MATERIAL:

Aluminum

### FINISHING:

Black + black ring

White + black ring

Black + bronze ring

White + bronze ring

### LIGHTING:

**LED** 

## **INPUT VOLTAGE:**

110-277V

### **IP RATING:**

20

### **DRIVER POSITION:**

Remote

### **OPERATING TEMPERATURE RANGE:**

-20 to +40 C













<u>TECHNICAL</u>

OUTDOOR





**CONTACT US:** 

sales@gordonbullard.com www.byiba.com 1 877-964-4646


WE WELCOME ALL CUSTOM ORDERS




**PROJECT** 

SPEC TYPE

NOTES















### **HOW TO ORDER:**

Example:

CODE: BY-2015-CL-01-BB-K30-DIM

### CODE:

BY-2015-CL-01-BB-

K30-DIM

## 1 MODEL:

-01 A) Diameter - Ø: 1.5" (3.5 cm) B) Height - H: 3.9" (9.9 cm)

-02 A) Diameter - Ø: 1.5" (3.5 cm) B) Height - H: 9.8" (25 cm)

## 2 LIGHT SOURCE:

LED / 8.6W / 250mA / 1100 lm / CRI 90 / 3000K

# 3 FINISH OPTIONS:

-BB Black + black ring
-WB White + black ring
-BBR Black + bronze ring
-WBR White + bronze ring

### 3 CCT:


-K27 2700K -K30 3000K -K40 4000K

### 4 DIMMING OPTIONS:

-DIM 0-10V

-NON Non-Dimmable

# 5 PHOTOMETRIC:



#### WWW.BULLARDCOLLECTION.COM

<u>TECHNICAL</u>

<u>OUTDOOR</u>

<u>DECORATIVE</u>



**CONTACT US:** 

sales@gordonbullard.com www.byiba.com 1 877-964-4646