

BYIBA
L I G H T



ABACO-S
(track)

BY-43-TR

PROJECT

SPEC TYPE

NOTES



GENERAL INFORMATION:

The ABACO-S Non-Magnetic Track system features 1-Circuit and 3-Circuit track profiles, available in lengths of 39.4" (100 cm), 78.7" (200 cm), and 118" (300 cm). With an operating voltage of 110-277V, the profiles come in white or black finishes, made from aluminum with an electrostatic powder coating.

The system includes five spotlight designs, offering wattages of 13W, 21W, 24W, 28W, 35W, 47W, and 65W. The spotlights are crafted from aluminum die-casting or steel, both with electrostatic powder coating. Available CCT options include 3000K, 4000K, and 5000K, with CRI options of 80 or 90. Spotlights come in white, black, or gray finishes.

MATERIAL:

AL, Electrostatic Powder Coating

FINISHING:

White, Black, Gray

LIGHTING:

LED

VOLTAGE:

110-277V

IP RATING:

20

OPERATING TEMPERATURE RANGE:

-20 to +40 C

WWW.BULLARDCOLLECTION.COM

TECHNICAL

OUTDOOR

DECORATIVE



WE WELCOME ALL CUSTOM ORDERS

CONTACT US:

sales@gordonbullard.com




www.byiba.com

1 877-964-4646

PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

CODE:

Example:
CODE: BY-43-TR-1-01-BL-65290-01-W2-K30-C80-B1-WL

BY-43-TR-1-01-
BL-65290-01-
W2-K30-C80-
B1-WL


1 CHOOSE TRACK MODEL:

1-Circuit Track Profile



- 1-01 L: 39.4" (100 cm)
- 1-02 L: 78.7" (200 cm)
- 1-03 L: 118" (300 cm)

3-Circuit Track Profile



- 2-01 L: 39.4" (100 cm)
- 2-02 L: 78.7" (200 cm)
- 2-03 L: 118" (300 cm)

2 FINISH OPTION TRACK PROFILE:

- BL Black
- WH White

WWW.BULLARDCOLLECTION.COM

TECHNICAL

OUTDOOR

DECORATIVE



WE WELCOME ALL CUSTOM ORDERS


CONTACT US:

sales@gordonbullard.com
www.byiba.com
1 877-964-4646

PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

Example:
CODE: BY-43-TR-1-01-BL-65130-13-03-K30-C90-WL

CODE:

BY-43-TR-1-01-
BL-65130-13-03-
K30-C90-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - -65130-13-03
 Dimensions: Ø: 7.87" (20 cm) x H: 3.5" (8.9 cm)
 Housing: AL. Die-Casting, Electrostatic Powder Coating
 Cover: PC
 Light Source: LED (SMD)
 Power & Currents: 24W / 600 mA
 Lumens: 1971 lm


CCT: -K30 - 3000K
 -K40 - 4000K
 -K50 - 5000K

CRI: -C80 - 80
 -C90 - 90

Finish Options: -WL - White
 -BL - Black

Operating temperature range - -20 to +40°C
 Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



WWW.BULLARDCOLLECTION.COM

- TECHNICAL
- OUTDOOR
- DECORATIVE



WE WELCOME ALL CUSTOM ORDERS


CONTACT US:

sales@gordonbullard.com
www.byiba.com
 1 877-964-4646

PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

Example:
CODE: BY-43-TR-1-01-BL-65130-13-03-K30-C90-WL

CODE:

BY-43-TR-1-01-
BL-65130-13-03-
K30-C90-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - **-65130-14-03**

Dimensions: Ø: 11.8" (30 cm) x H: 3.74" (9.5 cm)
Housing: AL. Die-Casting, Electrostatic Powder Coating
Cover: PC
Light Source: LED (SMD)
Power & Currents: 28W / 700 mA
Lumens: 2676 lm


CCT: **-K30 - 3000K**
-K40 - 4000K
-K50 - 5000K

CRI: **-C80 - 80**
-C90 - 90

Finish Options: **-WL - White**
-BL - Black

Operating temperature range - -20 to +40°C
Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



WWW.BULLARDCOLLECTION.COM

TECHNICAL

OUTDOOR

DECORATIVE



CONTACT US:


sales@gordonbullard.com
www.byiba.com
1 877-964-4646

WE WELCOME ALL CUSTOM ORDERS

PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

CODE:

Example:
CODE: BY-43-TR-1-01-BL-65130-13-03-K30-C90-WL

BY-43-TR-1-01-
BL-65130-13-03-
K30-C90-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - **-65130-01**

Dimensions: Ø: 7.87" (20 cm) x H: 1.57" (4 cm)

Housing: AL. Die-Casting, Electrostatic Powder Coating

Cover: PC

Light Source: LED (SMD)

Power & Currents: 28W / 700 mA

Lumens: 2281 lm

CCT: **-K30 - 3000K**

-K40 - 4000K

-K50 - 5000K

CRI: **-C80 - 80**

-C90 - 90

Finish Options: **-WL - White**


-BL - Black

-GR - Gray

Operating temperature range - -20 to +40°C

Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



LED



IP20



WWW.BULLARDCOLLECTION.COM

TECHNICAL

OUTDOOR

DECORATIVE



WE WELCOME ALL CUSTOM ORDERS

CONTACT US:

sales@gordonbullard.com


www.byiba.com

1 877-964-4646

PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

CODE:

Example:
CODE: BY-43-TR-1-01-BL-65130-13-03-K30-C90-WL

BY-43-TR-1-01-
BL-65130-13-03-
K30-C90-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - **-65130-11**

Dimensions: Ø: 4.72" (12 cm) x H: 1.57" (4 cm)

Housing: AL. Die-Casting, Electrostatic Powder Coating

Cover: PC

Light Source: LED (SMD)

Power & Currents: 13W / 350 mA

Lumens: 1104 lm

CCT: **-K30 - 3000K**

-K40 - 4000K

-K50 - 5000K

CRI: **-C80 - 80**

-C90 - 90


Finish Options: **-WL - White**

-BL - Black

Operating temperature range - -20 to +40°C

Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



WWW.BULLARDCOLLECTION.COM

TECHNICAL

OUTDOOR

DECORATIVE



WE WELCOME ALL CUSTOM ORDERS

CONTACT US:

sales@gordonbullard.com


www.byiba.com

1 877-964-4646

PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

Example:
CODE: BY-43-TR-1-01-BL-65130-13-03-K30-C90-WL

CODE:

BY-43-TR-1-01-
BL-65130-13-03-
K30-C90-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - -65130-12
 Dimensions: Ø: 5.91" (15 cm) x H: 1.57" (4 cm)
 Housing: AL Die-Casting, Electrostatic Powder Coating
 Cover: PC
 Light Source: LED (SMD)
 Power & Currents: 21W / 500 mA
 Lumens: 1604 lm


CCT: -K30 - 3000K
 -K40 - 4000K
 -K50 - 5000K

CRI: -C80 - 80
 -C90 - 90

Finish Options: -WL - White
 -BL - Black

Operating temperature range - -20 to +40°C
 Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



WWW.BULLARDCOLLECTION.COM

TECHNICAL

OUTDOOR

DECORATIVE



WE WELCOME ALL CUSTOM ORDERS


CONTACT US:

sales@gordonbullard.com
www.byiba.com
 1 877-964-4646

PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

CODE:

Example:
CODE: BY-43-TR-1-01-BL-65130-13-03-K30-C90-WL

BY-43-TR-1-01-
BL-65130-13-03-
K30-C90-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - -65130-13
 Dimensions: Ø: 7.87" (20 cm) x H: 1.57" (4 cm)
 Housing: AL. Die-Casting, Electrostatic Powder Coating
 Cover: PC
 Light Source: LED (SMD)
 Power & Currents: 24W / 600 mA
 Lumens: 1971 lm


CCT: -K30 - 3000K
 -K40 - 4000K
 -K50 - 5000K

CRI: -C80 - 80
 -C90 - 90

Finish Options: -WL - White
 -BL - Black

Operating temperature range - -20 to +40°C
 Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



WWW.BULLARDCOLLECTION.COM

TECHNICAL

OUTDOOR

DECORATIVE



CONTACT US:


sales@gordonbullard.com
www.byiba.com
 1 877-964-4646

WE WELCOME ALL CUSTOM ORDERS

PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

CODE:

Example:
CODE: BY-43-TR-1-01-BL-65130-13-03-K30-C90-WL

BY-43-TR-1-01-
BL-65130-13-03-
K30-C90-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - -65130-14
 Dimensions: Ø: 11.81" (30 cm) x H: 1.57" (4 cm)
 Housing: Steel, Electrostatic Powder Coating
 Cover: PC
 Light Source: LED (SMD)
 Power & Currents: 28W / 700 mA
 Lumens: 2676 lm


CCT: -K30 - 3000K
 -K40 - 4000K
 -K50 - 5000K

CRI: -C80 - 80
 -C90 - 90

Finish Options: -WL - White
 -BL - Black

Operating temperature range - -20 to +40°C
 Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



WWW.BULLARDCOLLECTION.COM

- TECHNICAL
- OUTDOOR
- DECORATIVE



CONTACT US:


sales@gordonbullard.com
www.byiba.com
 1 877-964-4646

WE WELCOME ALL CUSTOM ORDERS

PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

Example:
CODE: BY-43-TR-1-01-BL-65130-13-03-K30-C90-WL

CODE:

BY-43-TR-1-01-
BL-65130-13-03-
K30-C90-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - -65130-14-02

Dimensions: Ø: 11.81" (30 cm) x H: 1.57" (4 cm)

Housing: Steel, Electrostatic Powder Coating

Cover: PC

Light Source: LED (SMD)

Power & Currents: 28W / 700 mA

Lumens: 2676 lm


CCT: -K30 - 3000K
-K40 - 4000K
-K50 - 5000K

CRI: -C80 - 80
-C90 - 90

Finish Options: -WL - White
-BL - Black

Operating temperature range - -20 to +40°C
Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



WWW.BULLARDCOLLECTION.COM

TECHNICAL

OUTDOOR

DECORATIVE



WE WELCOME ALL CUSTOM ORDERS


CONTACT US:

sales@gordonbullard.com
www.byiba.com
1 877-964-4646

PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

CODE:

Example:
CODE: BY-43-TR-1-01-BL-65130-13-03-K30-C90-WL

BY-43-TR-1-01-
BL-65130-13-03-
K30-C90-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - -65130-15
 Dimensions: Ø: 15.75" (40 cm) x H: 1.57" (4 cm)
 Housing: Steel, Electrostatic Powder Coating
 Light Source: LED (SMD)
 Power & Currents: 35W / 800 mA
 Lumens: 3134 lm


CCT: -K30 - 3000K
 -K40 - 4000K
 -K50 - 5000K

CRI: -C80 - 80
 -C90 - 90

Finish Options: -WL - White
 -BL - Black

Operating temperature range - -20 to +40°C
 Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



WWW.BULLARDCOLLECTION.COM

- TECHNICAL
- OUTDOOR
- DECORATIVE



CONTACT US:


sales@gordonbullard.com
www.byiba.com
 1 877-964-4646

WE WELCOME ALL CUSTOM ORDERS

PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

CODE:

Example:
CODE: BY-43-TR-1-01-BL-65130-13-03-K30-C90-WL

BY-43-TR-1-01-
BL-65130-13-03-
K30-C90-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - -65130-15-02
 Dimensions: Ø: 15.75" (40 cm) x H: 2.17" (5.5 cm)
 Housing: Steel, Electrostatic Powder Coating
 Light Source: LED (SMD)
 Power & Currents: 35W / 800 mA
 Lumens: 3134 lm


CCT: -K30 - 3000K
 -K40 - 4000K
 -K50 - 5000K

CRI: -C80 - 80
 -C90 - 90

Finish Options: -WL - White
 -BL - Black

Operating temperature range - -20 to +40°C
 Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



WWW.BULLARDCOLLECTION.COM

- TECHNICAL
- OUTDOOR
- DECORATIVE



CONTACT US:



sales@gordonbullard.com
www.byiba.com
 1 877-964-4646

WE WELCOME ALL CUSTOM ORDERS

PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

Example:
CODE: BY-43-TR-1-01-BL-65130-13-03-K30-C90-WL

CODE:

BY-43-TR-1-01-
BL-65130-13-03-
K30-C90-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - -65130-16-02
 Dimensions: Ø: 19.69" (50 cm) x H: 2.17" (5.5 cm)
 Housing: AL. Extrude, Electrostatic Powder Coating
 Cover: PC
 Light Source: LED (SMD)
 Power & Currents: 47W / 980 mA
 Lumens: 4300 lm


CCT: -K30 - 3000K
 -K40 - 4000K
 -K50 - 5000K

CRI: -C80 - 80
 -C90 - 90

Finish Options: -WL - White
 -BL - Black

Operating temperature range - -20 to +40°C
 Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



WWW.BULLARDCOLLECTION.COM

- TECHNICAL
- OUTDOOR
- DECORATIVE



WE WELCOME ALL CUSTOM ORDERS



CONTACT US:

sales@gordonbullard.com
www.byiba.com
 1 877-964-4646

PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

Example:
CODE: BY-43-TR-1-01-BL-65130-13-03-K30-C90-WL

CODE:

BY-43-TR-1-01-
BL-65130-13-03-
K30-C90-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - -65130-17-02
 Dimensions: Ø: 23.62" (60 cm) x H: 2.17" (5.5 cm)
 Housing: AL. Extrude, Electrostatic Powder Coating
 Cover: PC
 Light Source: LED (SMD)
 Power & Currents: 65W / 1200 mA
 Lumens: 5949 lm


CCT: **-K30** - 3000K
-K40 - 4000K
-K50 - 5000K

CRI: **-C80** - 80
-C90 - 90

Finish Options: **-WL** - White
-BL - Black

Operating temperature range - -20 to +40°C
 Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



WWW.BULLARDCOLLECTION.COM

- TECHNICAL
- OUTDOOR
- DECORATIVE



WE WELCOME ALL CUSTOM ORDERS


CONTACT US:

sales@gordonbullard.com
www.byiba.com
 1 877-964-4646

PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

CODE:

Example:
CODE: BY-43-TR-1-01-BL-65130-13-03-K30-C90-WL

BY-43-TR-1-01-
BL-65130-13-03-
K30-C90-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - -65200

Dimensions: Ø: 23.62" (15 cm) x H: 1.61" (4.1 cm)

Housing: AL. Die-Casting, Electrostatic Powder Coating

Gear Box: AL. Die-Casting, Electrostatic Powder Coating

Cover: PC

Light Source: LED (SMD)

Power & Currents: 21W / 500 mA

Lumens: 1604 lm


CCT: -K30 - 3000K
-K40 - 4000K
-K50 - 5000K

CRI: -C80 - 80
-C90 - 90

Finish Options: -WL - White
-BL - Black

Operating temperature range - -20 to +40°C
Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



WWW.BULLARDCOLLECTION.COM

- TECHNICAL
- OUTDOOR
- DECORATIVE




CONTACT US:

sales@gordonbullard.com
www.byiba.com
1 877-964-4646


WE WELCOME ALL CUSTOM ORDERS

ACCESSORIES FOR 1 CIRCUIT TRACK:


-105
Feed-in Cap
 -BL - Black
 -WH - White




-106
End Cap
 -BL - Black
 -WH - White




-107
Straight Connector
 -BL - Black
 -WH - White




-108
L Connector
 -BL - Black
 -WH - White



-110
T Connector
 -BL - Black
 -WH - White



-111
X Connector
 -BL - Black
 -WH - White



-153
Adapter
 -BL - Black
 -WH - White




HOW TO ORDER:


Example:
 CODE: 105-WH

ACCESSORIES FOR 3CIRCUIT TRACK:


-305
Feed-in Cap
 -BL - Black
 -WH - White




-306
End Cap
 -BL - Black
 -WH - White




-307
Straight Connector
 -BL - Black
 -WH - White




-308
L Connector
 -BL - Black
 -WH - White




-310
T Connector
 -BL - Black
 -WH - White



-311
X Connector
 -BL - Black
 -WH - White



-351
Adapter
 -BL - Black
 -WH - White



HOW TO ORDER:

Example:
 CODE: -305-BL

WWW.BULLARDCOLLECTION.COM

- TECHNICAL
- OUTDOOR
- DECORATIVE



CONTACT US:

sales@gordonbullard.com
www.byiba.com
 1 877-964-4646

WE WELCOME ALL CUSTOM ORDERS