



MACARON (track)

BY-43-TR



**PROJECT** 

SPEC TYPE

**NOTES** 

















#### **GENERAL INFORMATION:**

The Macaron Non-Magnetic Track collection features 1-Circuit and 3-Circuit track profiles in three lengths: 39.4" (100 cm), 78.7" (200 cm), and 118" (300 cm), designed for a voltage range of 110-277V. Available in white or black finishes, the track profiles are made from aluminum (AL) with an electrostatic powder coating for durability.

This collection includes two spotlight models, each measuring  $\varnothing$  4.53" (11.5 cm) x W 2.6" (6.6 cm), with wattage options of 18W or 27W. The spotlights offer CCT choices of 3000K or 4000K, CRI options of 80 or 90, and are available in white, black, or gray finishes.

#### MATERIAL:

AL, Electrostatic Powder Coating

#### FINISHING:

White, Black

#### LIGHTING:

**LED** 

#### **VOLTAGE:**

110-277V

#### IP RATING:

20

### **OPERATING TEMPERATURE RANGE:**

-20 to +40 C



**TECHNICAL** 

<u>OUTDOOR</u>

**DECORATIVE** 





**CONTACT US:** 

sales@gordonbullard.com www.byiba.com 1 877-964-4646


WE WELCOME ALL CUSTOM ORDERS







39.37"/78.74"/118.11" 100cm/200cm/300cm













(2.9cm)

1.03"



### **HOW TO ORDER:**

Example:

CODE: BY-43-TR-1-01-BL-65070-03-K30-C80-B1-WL

CODE:

BY-43-TR-BL1-01-65560-0 1-K30-C80-WL

# 1 CHOOSE TRACK MODEL:

1-Circuit Track Profile



-1-01 L: 39.4" (100 cm)

-1-02 L: 78.7" (200 cm)

-1-03 L:118" (300 cm)

3-Circuit Track Profile



-2-01 L: 39.4" (100 cm)

-2-02 L: 78.7" (200 cm)

-2-03 L: 118" (300 cm)

# 2 FINISH OPTION TRACK PROFILE:

-BL Black -WH White

#### WWW.BULLARDCOLLECTION.COM

<u>technical</u> <u>outdoor</u>

**DECORATIVE** 



**CONTACT US:** 




**PROJECT** 

SPEC TYPE

**NOTES** 

















### **HOW TO ORDER:**

Example:

CODE: BY-43-TR-1-01-BL-65380-K30-C80-B1-WL

#### CODE:

BY-43-TR-BL1-01-65380-K30-C80-WL

# 1 CHOOSE TRACK HEAD:

#### **GENERAL INFORMATION**

CODE - -65380

Dimensions:  $\emptyset$ : 4.53" (11.5 cm) x W: 2.6" (6.6 cm) Housing: AL. Extrude, Electrostatic Powder Coating

Reflector: Lens
Light Source: LED (COB)
Power: 18W
Output Current 500 mA

CCT: -K30 - 3000K -K40 - 4000K

CRI: -C80 - 80 -C90 - 90

Beam Angle  $-B1 - 17.8^{\circ} = 1912 \text{ Im}$  and lumens:  $-B2 - 27.7^{\circ} = 1907 \text{ Im}$ 

 $-B3 - 43.8^{\circ} = 2021 \text{ lm}$ 


Finish options: -WL - White 🗍

-BL - Black T-GR - Gray

Operating temperature range - -20 to +40°C

Maintenance of lumen - L80 - 50 000 hours at 25 °C

#### PHOTOMETRICS:



# WWW.BULLARDCOLLECTION.COM





**CONTACT US:** 




**PROJECT** 

SPEC TYPE

**NOTES** 



















Example:

CODE: BY-50-TR-1-01-BL-65380-K30-C80-B1-WL

#### CODE:

BY-43-TR-BL1-01-65380-

K30-C80-WL

# 1 CHOOSE TRACK HEAD:

### GENERAL INFORMATION

CODE - -65381

Dimensions:  $\emptyset$ : 4.53" (11.5 cm) x W: 2.6" (6.6 cm) Housing: AL. Extrude, Electrostatic Powder Coating

Reflector: Lens
Light Source: LED (COB)
Power: 27W
Output Current 700 mA

CCT: -K30 - 3000K -K40 - 4000K

CRI: -C80 - 80

Beam Angle -B1 - 18.2°= 2527 lm and lumens: -B2 - 27.7° = 2599 lm

-C90 - 90

 $-B3 - 43.4^{\circ} = 2649 \text{ Im}$ 

Finish options: -WL - White 📆

-BL - Black -GR - Gray

Operating temperature range - -20 to +40°C


Maintenance of lumen - L80 - 50 000 hours at 25 °C

### PHOTOMETRICS:









| od/1000 <b>t</b> m                           | C180 C0            | 3    | 1106  | 1479           |
|----------------------------------------------|--------------------|------|-------|----------------|
| 90                                           | 180 90             | h(m) | E(lx) | D(mm)<br>43.4° |
| <b>*</b> *********************************** | #**                | 1    | 4755  | 796            |
| 45                                           | 45                 | 2    | 1189  | 1593           |
| 15° 1<br>od/1000lm                           | 419 15°<br>C180 C0 | 3    | 528   | 2389           |

#### WWW.BULLARDCOLLECTION.COM





**CONTACT US:** 



# **ACCESSORIES FOR 1 CIRCUIT TRACK:**


-105

Feed-in Cap

-BL - Black







-106 **End Cap** 

Black -BL -


-WH - White



-107 **Straight Connector** 

-BL -Black -WH - White






-108 **L** Connector

-BL - Black -WH - White






-110

T Connector -BL - Black

-WH - White








- 111

### X Connector

-BL -Black -WH - White








-153

# Adapter

-BL -Black -WH - White







### **HOW TO ORDER:**

Example:

CODE: 105-WH

# WWW.BULLARDCOLLECTION.COM

**TECHNICAL OUTDOOR DECORATIVE** 



**CONTACT US:** 



# **ACCESSORIES FOR 3CIRCUIT TRACK:**


-305

### Feed-in Cap

-BL - Black -WH - White








-306

# End Cap

-BL - Black -WH - White








-307

# Straight Connector

-BL - Black -WH - White








-308

# L Connector

-BL - Black -WH - White








-310

# T Connector

-BL - Black -WH - White








-311

### X Connector

-BL - Black -WH - White








-351

# Adapter

-BL - Black -WH - White







### **HOW TO ORDER:**

Example:

CODE: -305-BL

#### WWW.BULLARDCOLLECTION.COM

TECHNICAL
OUTDOOR
DECORATIVE



CONTACT US: