

ROLL (track)

BY-43-TR



SPEC TYPE

NOTES

















GENERAL INFORMATION:

The ROLL Non-Magnetic Track system is available in 1-Circuit and 3-Circuit track profiles, with lengths of 39.4" (100 cm), 78.7" (200 cm), and 118" (300 cm), operating at 110-277V. The profiles are available in white or black finishes, constructed from aluminum with an electrostatic powder coating.

It includes three spotlight models with the following dimensions:

- Ø: 2.56" (6.5 cm) x H: 6.5" (16.5 cm)
- Ø: 2.6" (7.1 cm) x H: 7.24" (18.4 cm)
- Ø: 3.27" (8.3 cm) x H: 7.4" (18.8 cm)

The spotlights are available in wattages of 20W, 23W, 24W, 27W, and 36W, with aluminum anodized specular silver reflectors or lenses. They come in CCT options of 3000K and 4000K, with CRI ratings of 80 or 90. Finish options for the spotlights include white and black.

MATERIAL:

AL, Electrostatic Powder Coating

FINISHING:

White, Black, Gray

LIGHTING:

LED

VOLTAGE:

110-277V

IP RATING:

20

OPERATING TEMPERATURE RANGE:

-20 to +40 C

WWW.BULLARDCOLLECTION.COM

<u>TECHNICAL</u>

<u>OUTDOOR</u>

DECORATIVE




CONTACT US:


sales@gordonbullard.com www.byiba.com 1 877-964-4646


WE WELCOME ALL CUSTOM ORDERS


























HOW TO ORDER:

Example:

CODE: BY-43-TR-1-01-BL-65341-01-K30-C90-B1-WL

CODE:

BY-43-TR-1-01-BL-65341-01-K30-C90-B1-WL

1 CHOOSE TRACK MODEL:

1-Circuit Track Profile



- -1-01 L: 39.4" (100 cm)
- -1-02 L: 78.7" (200 cm)
- -1-03 L:118" (300 cm)

3-Circuit Track Profile



- -2-01 L: 39.4" (100 cm)
- -2-02 L: 78.7" (200 cm)
- -2-03 L: 118" (300 cm)

2 FINISH OPTION TRACK PROFILE:

-BL Black -WH White

WWW.BULLARDCOLLECTION.COM








CONTACT US:



SPEC TYPE

NOTES

















HOW TO ORDER:

Example:

CODE: BY-43-TR-1-01-BL-65341-01-K30-C90-B1-WL

CODE: BY-43-TR-1-01-

BL-65341-01-K30-C90-B1-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - -65341-01

Dimensions: Ø: 2.56" (6.5 cm) x H: 6.5" (16.5 cm)

Housing: AL. Die-Casting, Electrostatic Powder Coating

Reflector: AL. Anodized Specular Silver

Light Source: LED (COB)
Power & Currents: 20W / 500 mA

CCT: -K30 - 3000K -K40 - 4000K

CRI: -C80 - 80 -C90 - 90


Beam Angle & -B1 - 15.8° = 2008 lm lumens: -B2 - 28.1° = 1818 lm -B3 - 40.0° = 1810 lm

Finish Options: -WL - White -BL - Black

Operating temperature range - -20 to +40°C

Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



WWW.BULLARDCOLLECTION.COM






CONTACT US:



SPEC TYPE

NOTES

















LENS

HOW TO ORDER:

Example:

CODE: BY-43-TR-1-01-BL-65341-01-K30-C90-B1-WL



BY-43-TR-1-01-BL-65341-01-K30-C90-B1-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - -65342-01

Dimensions: Ø: 2.6" (6.6 cm) x H: 6.81" (17.3 cm)

Housing: AL. Die-Casting, Electrostatic Powder Coating

Reflector: LENS
Light Source: LED (COB)
Power & Currents: 23W / 600 mA

CCT: -K30 - 3000K -K40 - 4000K

CRI: -C80 - 80

-C90 - 90


Beam Angle & -B1 - 26.2° = 2378 lm lumens: -B2 - 34.6° = 2332 lm -B3 - 48.9° = 2502 lm

Finish Options: -WL - White -BL - Black

Operating temperature range - -20 to +40°C

Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



WWW.BULLARDCOLLECTION.COM






CONTACT US:



SPEC TYPE

NOTES



















CODE: BY-43-TR-1-01-BL-65341-01-K30-C90-B1-WL

CODE:

BY-43-TR-1-01-BL-65341-01-K30-C90-B1-WL

CHOOSE TRACK HEAD: 3

GENERAL INFORMATION

CODE --65370-05

Ø: 2.6" (7.1 cm) x H: 7.24" (18.4 cm) Dimensions:

AL. Die-Casting, Electrostatic Powder Coating Housing:

Reflector: **LENS** Light Source: LED (COB) Power & Currents: 24W / 600 mA

CCT: -K30 - 3000K

-K40 - 4000K

CRI: -C80 - 80 -C90 - 90

Beam Angle & $-B1 - 23.5^{\circ} = 2610 \text{ lm}$ $-B2 - 31.0^{\circ} = 2623 \text{ Im}$ lumens:


 $-B3 - 47.2^{\circ} = 2675 \text{ Im}$

-WL - White Finish Options: -BL - Black

Operating temperature range - -20 to +40°C

Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



WWW.BULLARDCOLLECTION.COM






CONTACT US:



SPEC TYPE

NOTES



















Example:

CODE: BY-43-TR-1-01-BL-65341-01-K30-C90-B1-WL

CODE:

BY-43-TR-1-01-BL-65341-01-K30-C90-B1-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - -65170-05

Dimensions: Ø: 3.27" (8.3 cm) x H: 7.4" (18.8 cm)
Housing: AL. Die-Casting, Electrostatic Powder Coating

Reflector: LENS
Light Source: LED (COB)

Power & Currents: -W1 - 20W / 500 mA

-W2 - 27W / 700 mA -W3 - 36W / 900 mA

CCT: -K30 - 3000K -K40 - 4000K

CRI: -C80 - 80

-C90 - 90

Beam Angle & <u>For 20W model:</u> lumens: <u>-B1 - 20.0° = 2278 lm</u>

-B2 - 30.6° = 2299 lm -B3 - 50.7° = 2335 lm

For 27W model:

 $-B1 - 20^{\circ} = 2993 \text{ lm}$

 $-B2 - 30.7^{\circ} = 2086 \text{ lm}$

 $-B3 - 50.9^{\circ} = 3119 \text{ lm}$

For 36W model:

-B1 - 20.4°= 3455 lm

 $-B2 - 28.9^{\circ} = 3562 \text{ lm}$

 $-B3 - 46.1^{\circ} = 3600 \text{ lm}$

Finish Options: -WL - White

-BL - Black

Operating temperature range - -20 to +40°C

Maintenance of lumen - L80 - 50 000 hours at 25 °C

WWW.BULLARDCOLLECTION.COM

TECHNICAL OUTDOOR






CONTACT US:



SPEC TYPE

NOTES

















HOW TO ORDER:

Example:

CODE: BY-43-TR-1-01-BL-65341-01-K30-C90-B1-WL


CODE:


BY-43-TR-1-01-


BL-65341-01-K30-C90-B1-WL

PHOTOMETRICS:


For 20W model:




















For 36W model:







WWW.BULLARDCOLLECTION.COM

TECHNICAL

OUTDOOR

DECORATIVE



CONTACT US:




ACCESSORIES FOR 1 CIRCUIT TRACK:

-105

Feed-in Cap

-BL - Black -WH - White





-106 End Cap

-BL - Black


-WH - White



-107 Straight Connector

-BL - Black -WH - White






-108 L Connector

-BL - Black -WH - White






-110

T Connector

-BL - Black -WH - White








- 111

X Connector

-BL - Black







-153


Adapter

-BL - Black -WH - White









HOW TO ORDER:

Example:

CODE: 105-WH

WWW.BULLARDCOLLECTION.COM

TECHNICAL
OUTDOOR
DECORATIVE



CONTACT US:



ACCESSORIES FOR 3CIRCUIT TRACK:


-305

Feed-in Cap

-BL - Black -WH - White








-306

End Cap

-BL - Black -WH - White








-307

Straight Connector

-BL - Black -WH - White








-308

L Connector

-BL - Black -WH - White








-310

T Connector

-BL - Black -WH - White








-311

X Connector

-BL - Black -WH - White








-351

Adapter

-BL - Black -WH - White







HOW TO ORDER:

Example:

CODE: -305-BL

WWW.BULLARDCOLLECTION.COM

TECHNICAL

OUTDOOR

DECORATIVE



CONTACT US:

sales@gordonbullard.com www.byiba.com 1 877-964-4646

WE WELCOME ALL CUSTOM ORDERS