

BYIBA
L I G H T




SMOOTH
(track)

BY-43-TR

PROJECT

SPEC TYPE

NOTES



GENERAL INFORMATION:

The SMOOTH Non-Magnetic Track system comes in both 1-Circuit and 3-Circuit track profiles, with lengths of 39.4" (100 cm), 78.7" (200 cm), and 118" (300 cm). Operating at 110-277V, the track is made from aluminum with an electrostatic powder coating, available in white or black finishes.

Included are two spotlight models, each measuring \varnothing 5.35" (13.6 cm) x H 5.3" (13.5 cm), with wattage options of 20W or 28W for the reflector version, and 19W for the lens version. Spotlights feature an anodized specular silver reflector or a lens. CCT options are 3000K, 4000K, or 5000K, with CRI options of 80 or 90, available in white, black, or gray finishes.

MATERIAL:

AL, Electrostatic Powder Coating

FINISHING:

White, Black, Gray

LIGHTING:

LED

VOLTAGE:

110-277V

IP RATING:

20

OPERATING TEMPERATURE RANGE:

-20 to +40 C

WWW.BULLARDCOLLECTION.COM

TECHNICAL

OUTDOOR

DECORATIVE



WE WELCOME ALL CUSTOM ORDERS

CONTACT US:

sales@gordonbullard.com




www.byiba.com

1 877-964-4646

PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

CODE:

Example:
CODE: BY-43-TR-1-01-BL-65290-01-W2-K30-C80-B1-WL

BY-43-TR-1-01-
BL-65290-01-
W2-K30-C80-
B1-WL


1 CHOOSE TRACK MODEL:

1-Circuit Track Profile



- 1-01 L: 39.4" (100 cm)
- 1-02 L: 78.7" (200 cm)
- 1-03 L: 118" (300 cm)

3-Circuit Track Profile



- 2-01 L: 39.4" (100 cm)
- 2-02 L: 78.7" (200 cm)
- 2-03 L: 118" (300 cm)

2 FINISH OPTION TRACK PROFILE:

- BL Black
- WH White

WWW.BULLARDCOLLECTION.COM

- TECHNICAL
- OUTDOOR
- DECORATIVE



CONTACT US:

sales@gordonbullard.com
www.byiba.com
1 877-964-4646

WE WELCOME ALL CUSTOM ORDERS


PROJECT

SPEC TYPE

NOTES



REFLECTOR



HOW TO ORDER:

CODE:

Example:
CODE: BY-43-TR-1-01-BL-65290-01-W2-K30-C80-B1-WL

BY-43-TR-1-01-
BL-65290-01-
W2-K30-C80-
B1-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - -65290-01

Dimensions: Ø: 5.35" (13.6 cm) x H: 5.3" (13.5 cm)

Housing: AL. Die-Casting, Electrostatic Powder Coating

Reflector: AL. Anodized Specular Silver

Gear Box: AL. Die-Casting, Electrostatic Powder Coating

Light Source: LED (COB)

Power & Currents: **-W2** - 20W / 500 mA
-W3 - 28W / 700 mA

CCT: **-K30** - 3000K
-K40 - 4000K

CRI: **-C80** - 80
-C90 - 90

Beam Angle & lumens: For 20W model:
-B1 - 17.7° = 2277 lm
-B2 - 25.5° = 2244 lm
-B3 - 38.9° = 2284 lm

For 28W model:
-B1 - 17.8° = 3044 lm
-B2 - 26° = 3000 lm
-B3 - 39.2° = 3056 lm

Finish Options: **-WL** - White
-BL - Black
-GR - Gray

Operating temperature range - -20 to +40°C
Maintenance of lumen - L80 - 50 000 hours at 25 °C

WWW.BULLARDCOLLECTION.COM

- TECHNICAL
- OUTDOOR
- DECORATIVE



CONTACT US:

sales@gordonbullard.com
www.byiba.com
1 877-964-4646

WE WELCOME ALL CUSTOM ORDERS


PROJECT

SPEC TYPE

NOTES



LENS



HOW TO ORDER:

Example:
CODE: BY-43-TR-1-01-BL-65290-01-W2-K30-C80-B1-WL

CODE:

BY-43-TR-1-01-
BL-65290-01-
W2-K30-C80-
B1-WL

3 CHOOSE TRACK HEAD:

GENERAL INFORMATION

CODE - -65290-02
 Dimensions: Ø: 5.35" (13.6 cm) x H: 5.3" (13.5 cm)
 Housing: AL. Die-Casting, Electrostatic Powder Coating
 Reflector: Lens
 Gear Box: AL. Die-Casting, Electrostatic Powder Coating
 Light Source: LED (SMD)
 Power : 19W
 Output Current: 500 mA
 Luminous Flux: 1469 lm


CCT: -K30 - 3000K
 -K40 - 4000K
 -K50 - 5000K

CRI: -C80 - 80
 -C90 - 90

Finish Options: -WL - White
 -BL - Black
 -GR - Gray

Operating temperature range - -20 to +40°C
 Maintenance of lumen - L80 - 50 000 hours at 25 °C

PHOTOMETRICS:



WWW.BULLARDCOLLECTION.COM

TECHNICAL

OUTDOOR

DECORATIVE



WE WELCOME ALL CUSTOM ORDERS

CONTACT US:

sales@gordonbullard.com
www.byiba.com
 1 877-964-4646

PROJECT

SPEC TYPE

NOTES



REFLECTOR



LENS



HOW TO ORDER:

CODE:


Example:
CODE: BY-43-TR-1-01-BL-65290-01-W2-K30-C80-B1-WL

BY-43-TR-1-01-
BL-65290-01-
W2-K30-C80-
B1-WL






PHOTOMETRICS:

FOR REFLECTOR TYPE:


20W MODEL



28W MODEL



FOR LENS TYPE:



WWW.BULLARDCOLLECTION.COM

- TECHNICAL
- OUTDOOR
- DECORATIVE




CONTACT US:

sales@gordonbullard.com
www.byiba.com
1 877-964-4646


WE WELCOME ALL CUSTOM ORDERS

ACCESSORIES FOR 1 CIRCUIT TRACK:


-105
Feed-in Cap
 -BL - Black
 -WH - White




-106
End Cap
 -BL - Black
 -WH - White




-107
Straight Connector
 -BL - Black
 -WH - White




-108
L Connector
 -BL - Black
 -WH - White




-110
T Connector
 -BL - Black
 -WH - White



-111
X Connector
 -BL - Black
 -WH - White



-153
Adapter
 -BL - Black
 -WH - White



HOW TO ORDER:

Example:
 CODE: 105-WH

WWW.BULLARDCOLLECTION.COM

- TECHNICAL
- OUTDOOR
- DECORATIVE




CONTACT US:

sales@gordonbullard.com
www.byiba.com
 1 877-964-4646


WE WELCOME ALL CUSTOM ORDERS

ACCESSORIES FOR 3CIRCUIT TRACK:


-305
Feed-in Cap
 -BL - Black
 -WH - White




-306
End Cap
 -BL - Black
 -WH - White




-307
Straight Connector
 -BL - Black
 -WH - White




-308
L Connector
 -BL - Black
 -WH - White




-310
T Connector
 -BL - Black
 -WH - White



-311
X Connector
 -BL - Black
 -WH - White



-351
Adapter
 -BL - Black
 -WH - White



HOW TO ORDER:

Example:
 CODE: -305-BL

WWW.BULLARDCOLLECTION.COM

- TECHNICAL
- OUTDOOR
- DECORATIVE



CONTACT US:

sales@gordonbullard.com
www.byiba.com
 1 877-964-4646

WE WELCOME ALL CUSTOM ORDERS