



GLINDA (ceiling-mounted)

BY-4045C-PC



PROJECT

SPEC TYPE

NOTES



























GENERAL INFORMATION:

The GLINDA by BYIBA is a versatile recessed lighting fixture crafted from CRISTALY®, a durable and paintable material that allows for seamless integration into various interior designs. Designed for both ceiling and wall installations, it features a sleek, minimalist design that complements modern aesthetics. The fixture is compatible with GU10 LED bulbs, providing energy-efficient illumination suitable for dining rooms, living areas, bedrooms, kitchens, hallways, offices, restaurants, shops, and hotels. Its Italian craftsmanship and design excellence make the GLINDA 4045C a refined choice for both residential and commercial spaces.

MATERIAL:

CRISTALY®

FINISHING:

White

LIGHTING:

LED / GU 10

INPUT VOLTAGE:

110-277V / 110-120V

IP RATING:

IP20

DRIVER POSITION:

Remote

INSULATION CLASS:

 $\parallel / \parallel \parallel$

WWW.BULLARDCOLLECTION.COM

TECHNICAL OUTDOOR

DECORATIVE



CONTACT US:

sales@gordonbullard.com www.byiba.com 1 877-964-4646


WE WELCOME ALL CUSTOM ORDERS



PROJECT

SPEC TYPE

NOTES



HOW TO ORDER:

Example:

CODE: BY-4045C-PC-L1-K27-DIM

CODE:

BY-4045C-PC-L1-K27-DIM

DIMENSIONS:

A) Length L: 4.72" (12 cm) 7.87" (20 cm) B) Height -H: C) Length -7.87" (20 cm) L: D) Depth -4.33" (11 cm)

LIGHT SOURCE:

GU 10 / max. 20W / 110-120V -GU

LED / 6,5W / 110-277V / CRI 90 -L1 -L2 LED / 13W / 110-277V / CRI 90

CCT and LUMENS:

-KK40

-K27 2700K = 800 lm-K30 3000K = 850 lmFOR L1 MODEL -K40 4000K = 900 lm-KK27 2700K = 1500 lm-KK30 3000K = 1600 ImFOR L2 MODEL

DIMMING OPTIONS: (only for LED models)

4000K = 1700 Im

-DIM 0-10V -DALI DALI -LT Lutron -CS Casambi -WF WI-FI

-NON Non-Dimmable

































CONTACT US:

sales@gordonbullard.com www.byiba.com 1 877-964-4646