

LSV (linear)


BY-LSV-ARC



PROJECT

SPEC TYPE

NOTES





GENERAL INFORMATION:

Elevate your space with the LSV Series – a premium line of water-resistant, ultra-flexible linear lights, engineered for seamless integration into both interior and exterior architectural projects. Ideal for wellness zones, spas, showers, and outdoor environments, the LSV Series blends high performance with minimalist elegance.

MATERIAL:

Silicon estruded body and resin

FINISHING:

Natural Aluminum

LIGHTING:

LED

INPUT VOLTAGE:

110-277V

IP RATING:

67

DRIVER POSITION:

Remote

CRI:

CRI 90

OPERATING TEMPERATURE:

Ta min: -4°F to Ta max: +122°F

LIGHTING DISTRIBUTION:

120°

COVER:

Opal

WWW.BULLARDCOLLECTION.COM

<u>TECHNICAL</u>

<u>OUTDOOR</u>

DECORATIVE



CONTACT US:

sales@gordonbullard.com www.byiba.com 1 877-964-4646


WE WELCOME ALL CUSTOM ORDERS




PROJECT

SPEC TYPE

NOTES







HOW TO ORDER:

Example:

CODE: BY-LSV-ARC-BL1-L1-K27-DIM

CODE:

BY-LSV-ARC-BL1-L1-K27-DIM

BODY LENGHT:

-BL1 L: 11.8" (30 cm) 19.7" (50 cm) -BL2 L:

39.4" (100 cm) -BL3 L: -BL4 59" (150 cm) L:

-BL5 L: 78.7" (200 cm)

-CUS Custom on request*

2 **BODY HEIGHT & WIDTH:**

A) H: 1,06" (2,7 cm) x B) W: 0,75" (1,9 cm)

LIGHT SOURCE:

-L1 LED / 3W per ft. / 110-277V

LED RGB / 3W per ft. / 110-277V -L2

CCT & LUMENS:

-K30 $3000K = 190 \, \text{lm/ft}$

-K40 4000K = 212 lm/ft

-K50 5000K = 230 lm/ft

DIMMING OPTIONS:

-DIM 0-10V

-DALI DALI

-LT Lutron

-CS Casambi

WI-FI

-WF

-NON Non-Dimmable

WWW.BULLARDCOLLECTION.COM

TECHNICAL OUTDOOR

DECORATIVE



CONTACT US:

sales@gordonbullard.com www.byiba.com 1 877-964-4646