



# MILLI BIG (ceiling-mounted/wall)

BY-4193B-9010



**PROJECT** 

SPEC TYPE

**NOTES** 





#### GENERAL INFORMATION:

The MILLI BIG is a sleek recessed spotlight designed for modern interiors where minimal depth is essential. With a total thickness of just 0,59", this fixture offers high performance in tight installation spaces without compromising on light quality or build. If you need a recessed ceiling or wall light that delivers powerful LED output in an almost flush mount format, the MILLI BIG is ideal. Its shallow depth makes it perfect for low space constraints, while its solid construction materials and patented fixing system ensure a secure, high-quality installation. Elegant and efficient, it suits residential, commercial, or architectural programmes where minimalism meets performance.

#### MATERIAL:

**CRISTALY®** 

#### FINISHING:

White / Paintable

#### LIGHTING:

**LED** 

#### **INPUT VOLTAGE:**

110-277V

#### IP RATING:

IP 20 / IP 44

### **INSULATION CLASS:**

Ш

#### **DRIVER POSITION:**

Remote

#### WWW.BULLARDCOLLECTION.COM

<u>TECHNICAL</u>

<u>OUTDOOR</u>

DECORATIVE



**CONTACT US:** 


sales@gordonbullard.com www.byiba.com 1 877-964-4646



**PROJECT** 

SPEC TYPE

NOTES







# **HOW TO ORDER:**

Example:

CODE: BY-4193B-9010-L1-K27-P20-DIM

#### CODE:

BY-4193B-90 10-L1-K27-P20-DIM

# 1 DIMENSIONS:

A) Width - W: 0.98" (2.5 cm)
B) Length - L: 7.87" (20 cm)
C) Height - H: 9.84" (25 cm)

## 2 LIGHT SOURCE:

-L1 LED / max. 8W / 110-277V / CRI 85 -L2 LED / max. 16W / 110-277V / CRI 85

## 3 CCT and LUMENS:

-K27 2700K = 1050 lm-K30 3000K = 1100 lm for L1 model

-K40 4000K = 1160 lm

-KK27 2700K = 2090 lm

-KK30 3000K = 2200 lm } for L2 model

-KK40 4000K = 2330 lm

# 4 IP RATING:

-P20 IP 20 -P44 IP 40

#### 5 DIMMING OPTIONS:

**-DIM** 0-10V

-DALI DALI

-LT Lutron

-CS Casambi

-NON Non-Dimmable

#### WWW.BULLARDCOLLECTION.COM

TECHNICAL OUTDOOR

DECORATIVE



**CONTACT US:** 

sales@gordonbullard.com www.byiba.com 1 877-964-4646