



MILLI (ceiling-mounted/wall)

BY-4193-9010



PROJECT

SPEC TYPE

NOTES





GENERAL INFORMATION:

The Milli is an ultra-slim recessed ceiling/wall light designed for spaces where minimal depth is essential. With only 0,59" thickness, this fixture combines high performance LEDs, a premium diffusing plate, and a CRISTALY® frame with precision fixing wings to deliver clean, stable lighting even in tight installations. Rich in design and performance, this fixture allows you to maintain a clean, minimal aesthetic without compromising on light quality. The paintable CRISTALY® finish ensures the fixture can blend seamlessly with ceilings or walls when decorated with water-based paint. Its low profile makes it perfect for retrofit or new builds where space above drywall is tight. Whether for homes, offices, galleries or commercial interiors, it offers both flexibility and elegance.

MATERIAL:

CRISTALY®

FINISHING:

White / Paintable

LIGHTING:

LED

INPUT VOLTAGE:

110-277V

IP RATING:

IP 20 / IP 44

INSULATION CLASS:

Ш

DRIVER POSITION:

Remote

WWW.BULLARDCOLLECTION.COM

TECHNICAL OUTDOOR





CONTACT US:

sales@gordonbullard.com www.byiba.com 1 877-964-4646


WE WELCOME ALL CUSTOM ORDERS




PROJECT

SPEC TYPE

NOTES







HOW TO ORDER:

Example:

CODE: BY-4193-9010-L1-K27-P20-DIM

CODE:

BY-4193-9010-L1-K27-P20-DIM

1 DIMENSIONS:

A) Width - W: 1.10" (2.8 cm)
B) Length - L: 4.72" (12 cm)
C) Height - H: 7.87" (20 cm)

2 LIGHT SOURCE:

-L1 LED / max. 6.5W / 110-277V / CRI 90 -L2 LED / max. 13W / 110-277V / CRI 90

3 CCT and LUMENS:

-K27 2700K = 800 lm -K30 3000K = 850 lm -K40 4000K = 900 lm

-KK27 2700K = 1500 lm -KK30 3000K = 1600 lm -KK40 4000K = 1700 lm

4 IP RATING:

-**P20** IP 20 -**P44** IP 40

5 DIMMING OPTIONS:

-DIM 0-10V
-DALI DALI
-LT Lutron
-CS Casambi
-NON Non-Dimmable

WWW.BULLARDCOLLECTION.COM

TECHNICAL OUTDOOR

<u>DECORATIVE</u>



CONTACT US:

sales@gordonbullard.com www.byiba.com 1 877-964-4646